

Safety Data Sheet

according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL SIM Indicator Spray

UFI: S38D-VMCP-V00Y-KY2H

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

indicator

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

Supplier

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk
Internet:

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

acetone; propan-2-one; propanone

2-butoxyethanol; ethylene glycol monobutyl ether

isopropanol (isopropyl alcohol)

Signal word: Danger

Pictograms:







Safety Data Sheet

according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 2 of 15

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Restricted to professional users.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





Hazard statements

H222-H229

Precautionary statements

P210-P211-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 3 of 15

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP	Regulation)	•	
67-64-1	acetone; propan-2-one;	propanone		25 - < 50 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2,	STOT SE 3; H225 H319 H336 EUH0	966	
64-17-5	ethanol, ethyl alcohol			12,5 - < 20 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2;	H225 H319	•	
74-98-6	propane			12,5 - < 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Compress	ed gas; H220 H280	•	
111-76-2	2-butoxyethanol; ethyler	ne glycol monobutyl ether		12,5 - < 20 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 3, Acute Tox	x. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H30	2 H315 H319	
106-97-8	butane (<0,1 % butadier	ne)		5 - < 10 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compress	ed gas; H220 H280		
75-28-5	isobutane			5 - < 10 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compress	ed gas; H220 H280	•	
67-63-0	isopropanol (isopropyl a	lcohol)		< 2,5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2,	STOT SE 3; H225 H319 H336	•	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

Specific Co	nic. Linnis, ivi-ia	ctors and ATE				
CAS No	EC No	Chemical name	Quantity			
	Specific Conc.	Limits, M-factors and ATE				
67-64-1	7-64-1 200-662-2 acetone; propan-2-one; propanone					
	inhalation: LC mg/kg	50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800				
64-17-5	200-578-6	ethanol, ethyl alcohol	12,5 - < 20 %			
	inhalation: LC	50 = 20000 mg/l (vapours); oral: LD50 = 7060 mg/kg				
111-76-2	203-905-0	2-butoxyethanol; ethylene glycol monobutyl ether	12,5 - < 20 %			
	inhalation: AT	E 3 mg/l (vapours); oral: ATE 1200 mg/kg				
67-63-0	200-661-7	isopropanol (isopropyl alcohol)	< 2,5 %			
	inhalation: LC	50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.



according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 4 of 15

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.



Safety Data Sheet

according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 5 of 15

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

indicator

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 6 of 15

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
1	• • • • • • • • • • • • • • • • • • •					

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol		Post shift



according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 7 of 15

DNEL/DMEL values

CAS No Substan	CE CONTRACTOR CONTRACT			
DNEL type		Exposure route	Effect	Value
67-64-1 acetone	; propan-2-one; propanone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-to	erm	inhalation	systemic	200 mg/m³
Consumer DNEL, long-to	erm	dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-to	erm	oral	systemic	62 mg/kg bw/day
ī				
64-17-5 ethanol,	ethyl alcohol			
Worker DNEL, long-term		inhalation	systemic	950 mg/m³
Worker DNEL, acute		inhalation	local	1900 mg/m³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-to	erm	inhalation	systemic	114 mg/m³
Consumer DNEL, acute		inhalation	local	950 mg/m³
Consumer DNEL, long-to	erm	dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-to	erm	oral	systemic	87 mg/kg bw/day
111-76-2 2-butoxy	vethanol; ethylene glycol monobutyl ether			
Consumer DNEL, acute		oral	systemic	13,4 mg/kg bw/day
Consumer DNEL, long-to	erm	oral	systemic	3,2 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	75 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	44,5 mg/kg bw/day
Consumer DNEL, long-to	erm	dermal	systemic	38 mg/kg bw/day
Worker DNEL, acute		inhalation	local	246 mg/m³
Worker DNEL, long-term		inhalation	systemic	98 mg/m³
Consumer DNEL, acute		inhalation	systemic	633 mg/m³
Worker DNEL, acute		inhalation	systemic	633 mg/m³
Consumer DNEL, acute		inhalation	local	123 mg/m³
Consumer DNEL, long-to	erm	inhalation	systemic	49 mg/m³
67-63-0 isopropa	nol (isopropyl alcohol)			
Consumer DNEL, long-to	erm	inhalation	systemic	89 mg/m³
Consumer DNEL, long-to	erm	dermal	systemic	319 mg/kg bw/da
Consumer DNEL, long-to	erm	oral	systemic	26 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/da
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³



Safety Data Sheet

according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 8 of 15

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine wate	er	1,06 mg/l
Freshwater	sediment	30,4 mg/kg
Marine sedi	ment	3,04 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	100 mg/l
Soil		29,5 mg/kg
64-17-5	ethanol, ethyl alcohol	
Freshwater		0,96 mg/l
Marine wate	or .	0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary p	poisoning	0,72 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg
67-63-0	isopropanol (isopropyl alcohol)	
Freshwater		140,9 mg/l
Marine wate	er	140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary p	poisoning	160 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	2251 mg/l
Soil		28 mg/kg

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Recommended glove articles:

FKM (fluoro rubber), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.



Safety Data Sheet

according to UK REACH Regulation

DINITROL SIM Indicator Spray

Product code: 21710 Revision date: 15.04.2025 Page 9 of 15

Protect skin by using skin protective cream.

Skin protection

. Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A2/P3

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol Colour: red

Odour: like: Solvent Odour threshold: not determined

Test method

Melting point/freezing point: not determined Boiling point or initial boiling point and

-44 °C

boiling range:

Flammability: not applicable Lower explosion limits: 1,1 vol. % Upper explosion limits: 15 vol. %

Flash point: not applicable DIN 53213

Auto-ignition temperature: 240 °C Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: The study does not need to be conducted

because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 3500 hPa

(at 20 °C)

Density (at 20 °C): 0,7 g/cm3 DIN 51757

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties not determined

No data available Sustained combustibility:

Self-ignition temperature

Solid: not applicable not applicable Gas:

Oxidizing properties not determined

Other safety characteristics

Evaporation rate: not determined Solvent content: 98,7 % Solid content: 0,5 % Viscosity / dynamic: not determined

Further Information



Safety Data Sheet

according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 10 of 15

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) 4340 ppm

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-64-1	acetone; propan-2-one; p	one; propan-2-one; propanone						
	oral	LD50 mg/kg	5800	Rat	RTECS			
	dermal	LD50 15800 mg/	7426- ′kg	Rabbit	IUCLID			
	inhalation (4 h) vapour	LC50	76 mg/l	Rat				
64-17-5	ethanol, ethyl alcohol							
	oral	LD50 mg/kg	7060	Rat				
	inhalation (4 h) vapour	LC50 mg/l	20000	Rat				
111-76-2	2-butoxyethanol; ethylen	e glycol mor	nobutyl ether					
	oral	ATE 1200	mg/kg					
	inhalation vapour	ATE 3 mg	ı/I					
67-63-0	isopropanol (isopropyl al	cohol)						
	oral	LD50 mg/kg	4570	Rat				
	dermal	LD50 mg/kg	13400	Rabbit				
	inhalation (4 h) vapour	LC50	30 mg/l	Rat				

Irritation and corrosivity



according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 11 of 15

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone						
	Acute fish toxicity	LC50 mg/l	5540		Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna		
	Algae toxicity	NOEC mg/l	4740		Selenastrum capricornutum		
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether						
	Acute fish toxicity	LC50 mg/l	1490	96 h	Lepomis macrochirus		

12.2. Persistence and degradability

The product has not been tested.

The product has not been tested.				
CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.



Safety Data Sheet

according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 12 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether	0,81 (25°C)
75-28-5	isobutane	2,8
67-63-0	isopropanol (isopropyl alcohol)	0,05

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.





according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 13 of 15

Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity:1 LExcepted quantity:E0Transport category:2Tunnel restriction code:D

Other applicable information (land transport)

F0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant: yes

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

 14.3. Transport hazard class(es):
 2.1

 14.4. Packing group:

 Hazard label:
 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

Other applicable information (air transport)

E0

Passenger-LQ: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Environmental properties

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable



Safety Data Sheet

according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 14 of 15

Other applicable information

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from" class

1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class

2

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class

2.

Category C, Clear of living quarters.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 98,7 % paints and varnishes: 690,9 g/l

Information according to Directive P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

Additional information: E2

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the relevant national contact point.

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,8,9,11,15,16.



according to UK REACH Regulation

DINITROL SIM Indicator Spray

Revision date: 15.04.2025 Product code: 21710 Page 15 of 15

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Compressed gas

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Skin Irrit: Skin irritation Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

	<u> </u>
Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Acute Tox. 4; H332	Bridging principle "Aerosols"
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)