

# DINITROL 460

## Permanent flexible glass sealer

DINITROL 460 is a permanently elastic, UV-resistant sealing compound with a high solid matter content for vehicle repair. Ideal to seal non-bonded vehicle windows. It can also be used as a sealant between rubber profiles and bodywork joints, in addition to sealing glass sunroofs. Once dry, the sealer is permanently elastic and does not become brittle. It is not harmful to chromium, paints and rubber parts.


» **Black**

» **Excess material can be dabbed off using the material**

» **High material compatibility**

» **Resistant to water and alkaline solutions**

» **Remains slightly elastic and sticky on the surface**



### Equipment

**DINITROL Industrial Nitrile Gloves XL**  
Art. No. 1734100

### DINITROL 460

| Art. No. | Size   | Package   | Color |
|----------|--------|-----------|-------|
| 12055    | 310 ml | Cartridge | Black |

# DINITROL 460

## Technical Details

### Product Description

DINITROL 460 is a permanently elastic, UV-resistant sealing compound with a high solid matter content for vehicle repair. Ideal for sealing non-bonded vehicle windows. DINITROL 460 can also be used as a sealant between rubber profiles and bodywork joints, in addition to sealing glass sunroofs. Once dry, the sealer is permanently elastic and does not become brittle. It is not harmful to chromium, paints and rubber parts.

### Application

Position the tip of the nozzle between the glass and the rubber seal or between metal and rubber profile and spray the sealer with a suitable cartridge gun. Excess sealer can be removed with a plastic spatula and wiped with a cloth soaked in petroleum spirit, or dabbed with a lint-free cloth

### Pre-Treatment Substrates

The surface to be treated must be free from oil, dust and grease.

For additional information, please consult DINOL GmbH.

## Technical Data

|                        |                          |
|------------------------|--------------------------|
| Colour                 | black                    |
| Base                   | rubber / synthetic resin |
| Density                | 1,45 g/cm <sup>3</sup>   |
| Flash point            | - 8°C                    |
| Solid content          | 71%                      |
| Temperature resistance | - 20°C to + 80°C         |
| Storage                | between 5°C – 25°C       |
| Storage time           | 24 months                |
| Hazard identification  | highly flammable         |
| Available in           | 310 ml Cartridge         |

### Hazards identification

#### 2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225; Skin Irrit. 2; H315; Aquatic Chronic 3; H412

**For all relevant safety advices please read the material safety data sheet or the packaging label.**