

DINITROL 6055 IQ

Thinner for polyester - putty DINITROL 6058 IQ

DINITROL 6055 IQ is a special thinner for the polyester putty DINITROL 6058 IQ. The thinner is used to achieve a smoother consistency on large surfaces and is a reactive thinner.

» **Transparent**

» **Thinner to adjust the viscosity of the 2C polyester putty**

» **Especially for DINITROL 11003 IQ LW FR, DINITROL 6058 IQ**

Equipment

DINITROL INDUSTRIAL NITRILE GLOVES XL
Art. No. 1734100

DINITROL 6055 IQ

Art. No.	Size	Package	Color
13122	5 L	Canister	Transparent

DINITROL 6055 IQ

Technical Details

Product description

DINITROL 6055 IQ is a special thinner for the polyester putty DINITROL 6058 IQ. The thinner is used to achieve a smoother consistency on large surfaces. DINITROL 6055 IQ is a reactive thinner, which polymerizes during the hardening with more than 80% and can cause in accordance to the added quantity a light shrinking. Do not add more than 10% DINITROL 6055 IQ, because a higher add-on can impair the adhesion on the substrate and the hardening of the putty.

Caution:

This thinner for polyester putties is not suitable as thinner for 2 K acrylic lacquer, alkyd resin lacquer, 2 K acrylic filler or 1K to base coat. To use only in well ventilated areas.

For additional information, please consult DINOL GmbH.

Technical Data

Colour	transparent
Base	liquid
Density	0.9 kg/L
Flash point	< 21°C
Water-dissolvable	no
Application quantity	3% up to max. 10%
Available in	5 L

Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226; Acute Tox. 4; H332; Asp. Tox. 1; H304; Skin Irrit. 2; H315; Eye Irrit. 2; H319; Repr. 2; H361d; STOT SE 3; H335; STOT RE 1; H372; Aquatic Chronic 3; H412

For all relevant safety advices please read the material safety data sheet or the packaging label.