

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

DINITROL 112

UFI: M7F9-NMUX-X005-5GC7

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Anti-corrosive coating

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

**Supplier**

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

**1.4. Emergency telephone number:** Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226  
 STOT SE 3; H336  
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**Regulation (EC) No 1272/2008**

**Hazard components for labelling**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Signal word:** Warning

**Pictograms:**



**Hazard statements**

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 2 of 14

H412 Harmful to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P243 Take action to prevent static discharges.  
 P280 Wear protective gloves and eye protection/face protection.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

**Special labelling**

Restricted to professional users.

**Labelling of packages where the contents do not exceed 125 ml**
**Signal word:** Warning

**Pictograms:**

**Hazard statements**

H412

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			45 - < 50 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether			< 1 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H302 H315 H319			
25307-17-9	2,2'-(9-Octadecenyloxy)bisethanol			< 1 %
	246-807-3		01-2119510876-35	
	Acute Tox. 4, Skin Corr. 1, Aquatic Chronic 1; H302 H314 H410			

Full text of H and EUH statements: see section 16.

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 3 of 14

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	45 - < 50 %
		inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
111-76-2	203-905-0	2-butoxyethanol; ethylene glycol monobutyl ether	< 1 %
		inhalation: ATE 3 mg/l (vapours); oral: ATE 1200 mg/kg	
25307-17-9	246-807-3	2,2'-(9-Octadecenyylimino)bisethanol	< 1 %
		oral: LD50 = >300 - 2000 mg/kg Aquatic Chronic 1; H410: M=1	

**Further Information**

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

In all cases of doubt, or when symptoms persist, seek medical advice.  
 Never give anything by mouth to an unconscious person or a person with cramps.  
 If unconscious but breathing normally, place in recovery position and seek medical advice.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

Change contaminated clothing.  
 After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).  
 Do NOT induce vomiting.  
 Call a physician immediately.  
 Put victim at rest, cover with a blanket and keep warm.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**
**5.1. Extinguishing media**
**Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

No further relevant information available.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 4 of 14

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Remove all sources of ignition.  
Do not breathe gas/fumes/vapour/spray.  
Avoid contact with skin, eyes and clothes.  
Use personal protection equipment.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).  
Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.  
Clear contaminated areas thoroughly.  
Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.  
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Do not allow uncontrolled discharge of product into the environment.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 5 of 14

**Hints on joint storage**

Not required.

**Further information on storage conditions**

Keep container tightly closed.

**7.3. Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 6 of 14

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	Consumer DNEL, long-term	oral	systemic	125 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	208 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	871 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	systemic	185 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether			
	Consumer DNEL, acute	oral	systemic	13,4 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	3,2 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	75 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	44,5 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	38 mg/kg bw/day
	Worker DNEL, acute	inhalation	local	246 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	systemic	98 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	systemic	633 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	systemic	633 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	local	123 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	systemic	49 mg/m <sup>3</sup>
25307-17-9	2,2'-(9-Octadecenylimino)bisethanol			
	Consumer DNEL, long-term	oral	systemic	0,179 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	0,179 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	1,76 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	systemic	0,621 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	Value
	Environmental compartment	
25307-17-9	2,2'-(9-Octadecenylimino)bisethanol	
	Freshwater	0,000214 mg/l
	Marine water	0,000021 mg/l
	Freshwater sediment	1,692 mg/kg
	Marine sediment	0,1692 mg/kg
	Micro-organisms in sewage treatment plants (STP)	1,5 mg/l

**8.2. Exposure controls**

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 7 of 14



**Appropriate engineering controls**

Provide adequate ventilation.  
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.  
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Eye glasses with side protection (DIN EN 166)

**Hand protection**

Tested protective gloves must be worn (EN ISO 374):  
 FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.  
 NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.  
 Thickness of the glove material : > 0,12 mm  
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
 Protective gloves have to be replaced at the first sign of deterioration.  
 Protect skin by using skin protective cream.

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.  
 gas filtering equipment (EN 141),. Filter material/medium: A

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light brown
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	154-193 °C
Flammability:	not determined
Lower explosion limits:	0,7 vol. %
Upper explosion limits:	6,0 vol. %
Flash point:	36 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined

pH-Value: The study does not need to be conducted because the substance is known to be insoluble in water.

Viscosity / kinematic: not determined

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

**Test method**

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 8 of 14

Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	3 hPa
(at 20 °C)	
Vapour pressure:	13 hPa
(at 50 °C)	
Density (at 20 °C):	0,875 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not applicable

**9.2. Other information**

**Information with regard to physical hazard classes**

**Explosive properties**

The product is: not explosive.. In use, may form flammable/explosive vapour-air mixture.

**Sustained combustibility:**

No data available

**Oxidizing properties**

Not oxidising.

**Other safety characteristics**

**Evaporation rate:**

not determined

**Solvent separation test:**

not determined

**Solvent content:**

40,9 %

**Solid content:**

58,2 %

**Softening point:**

not determined

**Viscosity / dynamic:**

not determined

**Flow time:**

65 4 DIN 53211

(at 20 °C)

**Further Information**

No information available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

No further relevant information available.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Carbon monoxide

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix tested**

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 9 of 14

	Dose	Species	Source
LC50, inhalation (vapour) (4 h)	> 375 mg/l		

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 5000 mg/l	Rat		
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether				
	oral	ATE 1200 mg/kg			
	inhalation vapour	ATE 3 mg/l			
25307-17-9	2,2'-(9-Octadecenylimino)bisethanol				
	oral	LD50 >300 - 2000 mg/kg	Rat		

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
 Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.  
 Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
 Carcinogenicity: Based on available data, the classification criteria are not met.  
 Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C9-C 11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No information available.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 10 of 14

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether					
	Acute fish toxicity	LC50 mg/l	1490	96 h	Lepomis macrochirus	

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
		80%		
	Readily biodegradable (according to OECD criteria).			

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether	0,81 (25°C)

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

**List of Wastes Code - residues/unused products**

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 11 of 14

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Remove according to the regulations.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 Transport category: 3  
 Hazard No: 30  
 Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** Coating solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L  
 Excepted quantity: E1

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 12 of 14

Marine pollutant: no  
 Special Provisions: 955  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 10 L  
 Passenger LQ: Y344  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 355  
 IATA-max. quantity - Passenger: 60 L  
 IATA-packing instructions - Cargo: 366  
 IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning : Flammable liquids

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**Other applicable information**

Transport classification ADR/IMDG is based on packaging >30ltr(IMDG), <450ltr(ADR).  
 For other packaging untils different classification can apply.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 40,89 %  
 357,8 g/l  
 Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

Observe in addition any national regulations!  
 Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

**National regulatory information**

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 13 of 14

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

**Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

602286

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 8,16.

**Abbreviations and acronyms**

- Flam. Liq. 3: Flammable liquids, hazard category 3
- Acute Tox. 3: Acute toxicity, hazard category 3
- Acute Tox. 4: Acute toxicity, hazard category 4
- Asp. Tox. 1: Aspiration hazard, hazard category 1
- Skin Irrit. 2: Skin irritation, hazard category 2
- Skin Corr. 1: Skin corrosion, hazard category 1
- Eye Irrit. 2: Eye irritation, hazard category 2
- STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
- Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
- Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

**DINITROL 112**

Revision: 15.01.2026

Product code: 21608

Page 14 of 14

H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet contains only safety-related information and does not replace product information or product specifications.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*