

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

DINITROL 448 light grey

UFI: 75KJ-D468-2008-3PA8

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Anti-corrosive coating

1.3. Details of the supplier of the safety data sheet
Manufacturer

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

Supplier

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

1.4. Emergency telephone number: Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements
Regulation (EC) No 1272/2008
Hazard statements

H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Precautionary statements

P273	Avoid release to the environment.
------	-----------------------------------

Special labelling

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml
Hazard statements

H412

2.3. Other hazards

No information available.

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 2 of 14

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
13463-67-7	titanium dioxide			1 - < 5 %
	236-675-5		01-2119489379-17	
64-17-5	Ethanol			1 - < 5 %
	200-578-6		01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7779-90-0	trizinc bis(orthophosphate)			< 1 %
	231-944-3	030-011-00-6	01-2119485044-40	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
1314-13-2	zinc oxide			< 1 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)			< 0.0015 %
	-	613-167-00-5	01-2120764691-48	
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			
2634-33-5	1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one			< 0.036 %
	220-120-9	613-088-00-6	01-2120761540-60	
	Acute Tox. 2, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H302 H315 H318 H317 H400 H410			

Full text of H and EUH statements: see section 16.

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
13463-67-7	236-675-5	titanium dioxide	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
64-17-5	200-578-6	Ethanol	1 - < 5 %
		inhalation: LC50 = > 50 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
7779-90-0	231-944-3	trizinc bis(orthophosphate)	< 1 %
		inhalation: LC50 = > 5,7 mg/l (dusts or mists); oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
1314-13-2	215-222-5	zinc oxide	< 1 %
		inhalation: LC50 = > 2500 mg/l (dusts or mists); oral: LD50 = > 7950 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
55965-84-9	-	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	< 0.0015 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: ATE = 50 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 Aquatic Acute 1; H400: M=100 Aquatic Chronic 1; H410: M=100	
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one	< 0.036 %
		inhalation: ATE 0,21 mg/l (dusts or mists); oral: ATE 450 mg/kg Skin Sens. 1A; H317: >= 0,036 - 100 Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	

Further Information

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are therefore not given, as there is no longer any risk of inhalation of these substances (when handling this mixture).

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

In all cases of doubt, or when symptoms persist, seek medical advice.
 Never give anything by mouth to an unconscious person or a person with cramps.
 If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
 In case of irregular breathing or respiratory arrest provide artificial respiration.

After contact with skin

Change contaminated clothing.
 Wash with plenty of water/Soap.
 Do not wash with: Solvent/Thinner.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 4 of 14

Do NOT induce vomiting.
 Call a physician immediately.
 Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

No further relevant information available.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Special danger of slipping by leaking/spilling product.
 Ventilate affected area.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.
 In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).
 Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
 Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.
 Clear contaminated areas thoroughly.
 Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7
 Personal protection equipment: see section 8
 Disposal: see section 13

SECTION 7: Handling and storage

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 5 of 14

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

No special measures are necessary.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No special measures are necessary.

Hints on joint storage

Not required.

Further information on storage conditions

storage temperature: >0° - < 30°C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7727-43-7	Barium sulphate, respirable dust	-	4		TWA (8 h)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
13463-67-7	Titanium dioxide, total inhalable	-	10		TWA (8 h)	WEL

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 6 of 14

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7727-43-7	Barium sulfate			
Worker DNEL, long-term		inhalation	systemic	10 mg/m ³
Worker DNEL, long-term		inhalation	local	10 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	10 mg/m ³
Consumer DNEL, long-term		oral	systemic	13000 mg/kg bw/day
64-17-5	Ethanol			
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m ³
Worker DNEL, long-term		inhalation	systemic	950 mg/m ³
Worker DNEL, acute		inhalation	local	1900 mg/m ³
Consumer DNEL, acute		inhalation	local	950 mg/m ³
7779-90-0	trizinc bis(orthophosphate)			
Worker DNEL, long-term		inhalation	systemic	5 mg/m ³
Worker DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m ³
Consumer DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,83 mg/kg bw/day
1314-13-2	zinc oxide			
Worker DNEL, long-term		inhalation	systemic	5 mg/m ³
Worker DNEL, long-term		inhalation	local	0,5 mg/m ³
Worker DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m ³
Consumer DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,83 mg/kg bw/day

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 7 of 14

PNEC values

CAS No	Substance	Value
Environmental compartment		
7727-43-7	Barium sulfate	
Freshwater		0,115 mg/l
Freshwater sediment		600,4 mg/kg
Micro-organisms in sewage treatment plants (STP)		62,2 mg/l
Soil		207,7 mg/kg
64-17-5	Ethanol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
7779-90-0	trizinc bis(orthophosphate)	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Freshwater sediment		117,8 mg/kg
Marine sediment		56,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,100 mg/l
Soil		35,6 mg/kg
1314-13-2	zinc oxide	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Freshwater sediment		117,8 mg/kg
Marine sediment		56,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,100 mg/l
Soil		35,6 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):
 FKM (fluoro rubber), Breakthrough time:: 480 min.

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 8 of 14

NBR (Nitrile rubber), Breakthrough time:: 480 min.
 Thickness of the glove material : > 0,12 mm
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
 Protective gloves have to be replaced at the first sign of deterioration.
 Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	light grey	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		100 °C
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		not applicable
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		8
Viscosity / kinematic:		not determined
Water solubility:		completely miscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		23 hPa
(at 20 °C)		
Density (at 20 °C):		1,45 - 1,49 g/cm ³
Relative vapour density:		not determined
Particle characteristics:		not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

Other safety characteristics

Evaporation rate:	not determined
Solvent content:	2,4 %, water: 22,5 %
Solid content:	66 - 70 %
Sublimation point:	not determined
Softening point:	not determined

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 9 of 14

Pour point: not determined
 Viscosity / dynamic: 4500 - 5200 mPa·s

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No known hazardous reactions.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 10 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
13463-67-7	titanium dioxide				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
64-17-5	Ethanol				
	oral	LD50 10470 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 50 mg/l	Rat		
7779-90-0	trizinc bis(orthophosphate)				
	oral	LD50 > 5000 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 > 5,7 mg/l	Rat		
1314-13-2	zinc oxide				
	oral	LD50 > 7950 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 > 2500 mg/l	Rat		
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)				
	oral	ATE 100 mg/kg			
	dermal	ATE 50 mg/kg			
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			
2634-33-5	1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one				
	oral	ATE 450 mg/kg			
	inhalation dust/mist	ATE 0,21 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 11 of 14

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	Ethanol					
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna (Big water flea)	
1314-13-2	zinc oxide					
	Acute fish toxicity	LC50 mg/l	1120	96 h	fish	GESTIS
	Acute crustacea toxicity	EC50 mg/l	12,3	48 h		GESTIS

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 12 of 14

Disposal recommendations

Dispose of waste according to applicable legislation.
Do not mix with other wastes.

Contaminated packaging

Completely emptied packages can be recycled.
Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

- 14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

- 14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.
 - 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
 - 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
 - 14.4. Packing group:** No dangerous good in sense of this transport regulation.
- Marine pollutant: no
Segregation group: 4 - chlorates

Air transport (ICAO-TI/IATA-DGR)

- 14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 2,43 % (36 g/l)

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 13 of 14

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,8,9,11,16.

Abbreviations and acronyms

- Flam. Liq. 2: Flammable liquids, hazard category 2
- Acute Tox. 2: Acute toxicity, hazard category 2
- Acute Tox. 3: Acute toxicity, hazard category 3
- Acute Tox. 4: Acute toxicity, hazard category 4
- Skin Corr. 1C: Skin corrosion, sub-category 1C
- Skin Irrit. 2: Skin irritation, hazard category 2
- Eye Dam. 1: Serious eye damage, hazard category 1
- Eye Irrit. 2: Eye irritation, hazard category 2
- Skin Sens. 1A: Skin sensitisation, hazard category 1A
- Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
- Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
- Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

- H225 Highly flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.

DINITROL 448 light grey

Revision: 18.12.2025

Product code: 5112

Page 14 of 14

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)