

DINITROL 7225 AUTOCLEANER

Cleaner

DINITROL 7225 AUTOCLEANER efficiently cleans and dissolves fats, waxes, engine and diesel oils. It can be used on most metal parts. Before use, make sure parts and components are compatible with this product.

- » Transparent
- » Low aromatic
- » High flash point
- » Self separating
- » Efficient



DINITROL 7225 AUTOCLEANER

Art. No.	Size	Package	Color
15003	100 ml	Bottle	Transparent
15002	20 L	Canister	Transparent

DINITROL 7225 AUTOCLEANER

Technical Details

Product description

DINITROL 7225 AUTOCLEANER efficiently cleans and dissolves fats, waxes, engine and diesel oils.

Applications

DINITROL 7225 AUTOCLEANER can be used on most metal parts. Before use, make sure parts and components are compatible with DINITROL 7225 AUTOCLEANER.

Method of Use

DINITROL 7225 AUTOCLEANER may be applied by spraying, brushing or dipping. During spray application care must be taken to prevent electrostatic discharges and occupational exposure to aerosol. Allow DINITROL 7225 AUTOCLEANER to work for a few minutes, then rinse with cold water. Old, oxidised corrosion protection films may need additional time to dissolve. For additional information, please consult DINOL GmbH.

Storage

When the product is stored cool and dry, it will have a shelf life of at least 2 years when stored in unopened original packages.

Safety precautions

Additional information can be found in the safety data sheet.

Transportation

Additional information can be found in the safety data sheet.

Technical Data

Colour	transparent
Density at 23°C	790 kg/m ³
Flash point	> 61°C
Recommended film thickness wet	not applicable
Available in	100 ml Bottles, 20 L Kanister, 208 L Drum

Hazards identification

2.1. Classification of the substance or mixture
GB CLP Regulation
Asp. Tox. 1; H304

For all relevant safety advices please read the material safety data sheet or the packaging label.