

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

DINITROL 3650

UFI: N84A-NMY6-Y00E-7441

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet
Manufacturer

| | | |
|-------------------------|----------------------|--------------------------------|
| Company name: | DINOL GmbH | |
| Street: | Pyrmonter Strasse 76 | |
| Place: | D-32676 Luegde | |
| Telephone: | + 49 (0) 5281 982980 | Telefax: + 49 (0) 5281 9829860 |
| E-mail: | msds@dinol.com | |
| Contact person: | Labor | |
| Internet: | www.dinol.com | |
| Responsible Department: | msds@dinol.com | |

Supplier

| | |
|---------------|----------------------------------|
| Company name: | Leading Solvent Supplies Limited |
| Street: | Marston Business Park, Rudgate |
| Place: | GB Tockwith, York YO26 7QF |
| E-mail: | enquiries@leading-solvents.co.uk |
| Internet: | www.leading-solvents.co.uk |

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

STOT SE 3; H336

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements
Regulation (EC) No 1272/2008
Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

Pictograms:

Hazard statements

H226

Flammable liquid and vapour.

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 2 of 13

H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH208 Contains calcium sulfonate. May produce an allergic reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P243 Take action to prevent static discharges.
 P280 Wear protective gloves and eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

Hazard statements

H304

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

| CAS No | Chemical name | Quantity |
|------------|--|-------------|
| | EC No | |
| | Index No | |
| | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 55 - < 60 % |
| | 919-857-5 | |
| | 01-2119463258-33 | |
| | Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066 | |
| 61789-86-4 | calcium sulfonate | 1 - < 5 % |
| | 263-093-9 | |
| | 01-2119488992-18 | |
| | Skin Sens. 1B; H317 | |
| 111-76-2 | 2-butoxyethanol; ethylene glycol monobutyl ether | < 1 % |
| | 203-905-0 | |
| | 603-014-00-0 | |
| | 01-2119475108-36 | |
| | Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H302 H315 H319 | |

Full text of H and EUH statements: see section 16.

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 3 of 13

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|------------|-----------|--|-------------|
| | | Specific Conc. Limits, M-factors and ATE | |
| | 919-857-5 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 55 - < 60 % |
| | | inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg | |
| 61789-86-4 | 263-093-9 | calcium sulfonate | 1 - < 5 % |
| | | dermal: LD50 = 4000 - 5000 mg/kg; oral: LD50 = 16000 mg/kg Skin Sens. 1B; H317: >= 10 - 100 | |
| 111-76-2 | 203-905-0 | 2-butoxyethanol; ethylene glycol monobutyl ether | < 1 % |
| | | inhalation: ATE 3 mg/l (vapours); oral: ATE 1200 mg/kg | |

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures
5.1. Extinguishing media
Suitable extinguishing media

Carbon dioxide (CO₂) Extinguishing powder. Water spray jet alcohol resistant foam.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use suitable breathing apparatus.

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 4 of 13

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.
Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.
Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No special measures are necessary.

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 5 of 13

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|----------|-----------------|-----|-------------------|-----------|---------------|--------|
| 111-76-2 | 2-Butoxyethanol | 25 | 123 | | TWA (8 h) | WEL |
| | | 50 | 246 | | STEL (15 min) | WEL |

Biological Monitoring Guidance Values (EH40)

| CAS No | Substance | Parameter | Value | Test material | Sampling time |
|----------|-----------------|--------------------------------|--------------|---------------|---------------|
| 111-76-2 | 2-Butoxyethanol | butoxyacetic acid (creatinine) | 240 mmol/mol | urine | Post shift |

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 6 of 13

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|---|-----------|----------------|----------|--------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | |
| Consumer DNEL, long-term | | oral | systemic | 125 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | systemic | 208 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | systemic | 125 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 871 mg/m ³ |
| Consumer DNEL, long-term | | inhalation | systemic | 185 mg/m ³ |
| 61789-86-4 calcium sulfonate | | | | |
| Worker DNEL, long-term | | dermal | systemic | 3,33 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | local | 1,03 mg/cm ² |
| Consumer DNEL, long-term | | inhalation | systemic | 2,9 mg/m ³ |
| Consumer DNEL, long-term | | dermal | systemic | 1,667 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | local | 0,513 mg/cm ² |
| Consumer DNEL, long-term | | oral | systemic | 0,8333 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 11,75 mg/m ³ |
| 111-76-2 2-butoxyethanol; ethylene glycol monobutyl ether | | | | |
| Consumer DNEL, acute | | oral | systemic | 13,4 mg/kg bw/day |
| Consumer DNEL, long-term | | oral | systemic | 3,2 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | systemic | 75 mg/kg bw/day |
| Consumer DNEL, acute | | dermal | systemic | 44,5 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | systemic | 38 mg/kg bw/day |
| Worker DNEL, acute | | inhalation | local | 246 mg/m ³ |
| Worker DNEL, long-term | | inhalation | systemic | 98 mg/m ³ |
| Consumer DNEL, acute | | inhalation | systemic | 633 mg/m ³ |
| Worker DNEL, acute | | inhalation | systemic | 633 mg/m ³ |
| Consumer DNEL, acute | | inhalation | local | 123 mg/m ³ |
| Consumer DNEL, long-term | | inhalation | systemic | 49 mg/m ³ |

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 7 of 13

PNEC values

| CAS No | Substance | |
|--|-------------------|-----------------|
| Environmental compartment | | Value |
| 61789-86-4 | calcium sulfonate | |
| Freshwater | | 1 mg/l |
| Marine water | | 1 mg/l |
| Freshwater sediment | | 226000000 mg/kg |
| Marine sediment | | 226000000 mg/kg |
| Secondary poisoning | | 16667 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 1000 mg/l |
| Soil | | 271000000 mg/kg |

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment
Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

Thickness of the glove material : > 0,12 mm

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: A

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

| | |
|------------------|----------------|
| Physical state: | Liquid |
| Colour: | beige |
| Odour: | characteristic |
| Odour threshold: | not determined |

Melting point/freezing point:

Test method
not determined

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 8 of 13

| | |
|---|--|
| Boiling point or initial boiling point and boiling range: | 154 - 193 °C |
| Flammability: | not determined |
| Lower explosion limits: | 0,6 vol. % |
| Upper explosion limits: | 7 vol. % |
| Flash point: | 41 °C DIN 53213 |
| Auto-ignition temperature: | > 200 °C |
| Decomposition temperature: | not determined |
| pH-Value: | The study does not need to be conducted because the substance is known to be insoluble in water. |
| Viscosity / kinematic: | not determined |
| Water solubility: | not applicable |
| Solubility in other solvents | not determined |
| Partition coefficient n-octanol/water: | not determined |
| Vapour pressure: | 3 hPa |
| (at 20 °C) | |
| Vapour pressure: | 13 hPa |
| (at 50 °C) | |
| Density (at 20 °C): | 0,83 g/cm ³ DIN 51757 |
| Relative vapour density: | not determined |
| Particle characteristics: | not applicable |

9.2. Other information

Information with regard to physical hazard classes

| | |
|---------------------------|-------------------|
| Explosive properties | not determined |
| Sustained combustibility: | No data available |
| Oxidizing properties | not determined |

Other safety characteristics

| | |
|----------------------|----------------|
| Solvent content: | 54,9 % |
| Solid content: | 45,9 % |
| Softening point: | not determined |
| Viscosity / dynamic: | 18 mPa·s |
| (at 20 °C) | |

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 9 of 13

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information
11.1. Information on hazard classes
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested

| | Dose | Species | Source |
|---------------------------------|------------|---------|--------|
| LC50, inhalation (vapour) (4 h) | > 256 mg/l | | |

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation dust/mist) > 12,5 mg/l

| CAS No | Chemical name | | | | |
|------------|---|------------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | |
| | oral | LD50 > 5000 mg/kg | Rat | | |
| | dermal | LD50 > 5000 mg/kg | Rabbit | | |
| | inhalation (4 h) vapour | LC50 > 5000 mg/l | Rat | | |
| 61789-86-4 | calcium sulfonate | | | | |
| | oral | LD50 16000 mg/kg | Rat | | |
| | dermal | LD50 4000 - 5000 mg/kg | Rabbit | | |
| 111-76-2 | 2-butoxyethanol; ethylene glycol monobutyl ether | | | | |
| | oral | ATE 1200 mg/kg | | | |
| | inhalation vapour | ATE 3 mg/l | | | |

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains calcium sulfonate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No information available.

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 10 of 13

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards
Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information
12.1. Toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | |
|----------|--|--------------|-----------|---------|---------------------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 111-76-2 | 2-butoxyethanol; ethylene glycol monobutyl ether | | | | | |
| | Acute fish toxicity | LC50 mg/l | 1490 | 96 h | Lepomis macrochirus | |

12.2. Persistence and degradability

There are no data available on the mixture itself.

| CAS No | Chemical name | | | |
|--------|---|-------|---|--------|
| | Method | Value | d | Source |
| | Evaluation | | | |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | |
| | | 80% | | |
| | Readily biodegradable (according to OECD criteria). | | | |

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|--|-------------|
| 111-76-2 | 2-butoxyethanol; ethylene glycol monobutyl ether | 0,81 (25°C) |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No further relevant information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 11 of 13

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 30
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Marine pollutant: no
 Special Provisions: 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 12 of 13

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Special Provisions: A3

Limited quantity Passenger: 10 L

Passenger LQ: Y344

Excepted quantity: E1

IATA-packing instructions - Passenger: 355

IATA-max. quantity - Passenger: 60 L

IATA-packing instructions - Cargo: 366

IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 54,90 %

paints and varnishes: 455,7 g/l

Information according to Directive P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information
Changes

DINITROL 3650

Revision: 09.03.2026

Product code: 21633

Page 13 of 13

This data sheet contains changes from the previous version in section(s): 16.

Abbreviations and acronyms

Flam. Liq. 3: Flammable liquids, hazard category 3
 Acute Tox. 3: Acute toxicity, hazard category 3
 Acute Tox. 4: Acute toxicity, hazard category 4
 Asp. Tox. 1: Aspiration hazard, hazard category 1
 Skin Irrit. 2: Skin irritation, hazard category 2
 Eye Irrit. 2: Eye irritation, hazard category 2
 Skin Sens. 1B: Skin sensitisation, hazard category 1B
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method

| Classification | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data |
| STOT SE 3; H336 | Calculation method |
| Asp. Tox. 1; H304 | Calculation method |

Relevant H and EUH statements (number and full text)

| | |
|--------|---|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| EUH208 | Contains calcium sulfonate. May produce an allergic reaction. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet contains only safety-related information and does not replace product information or product specifications.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)