

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 1 of 13

**1. Identification**
**Product identifier**

DINITROL 447 Black

**Recommended use of the chemical and restrictions on use**
**Use of the substance/mixture**

Anti-corrosive coating

**Details of the supplier of the safety data sheet**
**Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

**Supplier**

Company name:	DINOL U.S. Inc.	
Street:	8500 Cotter Street, Lewis Center	
Place:	USA-43035 Ohio	
Telephone:	740-548-1656	Telefax: 740-548-1657
E-mail:	info@dinolus.com	
Internet:	www.dinol.com	

**Emergency phone number:** 3E Company Emergency +1-866-404-4230

**2. Hazard(s) identification**
**Classification of the chemical**
**29 CFR Part 1910.1200**

Flammable liquids: Flam. Liq. 2  
 Carcinogenicity: Carc. 2  
 Skin corrosion/irritation: Skin Irrit. 2  
 Respiratory or skin sensitization: Skin Sens. 1  
 Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects)  
 Specific target organ toxicity repeated or prolonged exposure: STOT RE 2

**Label elements**
**29 CFR Part 1910.1200**
**Signal word:** Danger

**Pictograms:**

**Hazard statements**

Highly flammable liquid and vapor  
 Causes skin irritation  
 May cause an allergic skin reaction  
 May cause drowsiness or dizziness  
 Suspected of causing cancer  
 May cause damage to organs through prolonged or repeated exposure

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 2 of 13

**Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Keep container tightly closed.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash water thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin: Wash with plenty of water.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 Take off contaminated clothing and wash it before reuse.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If exposed or concerned: Get medical advice/attention.  
 In case of fire: Use water to extinguish.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.

**Hazards not otherwise classified**

No information available.

**3. Composition/information on ingredients**
**Mixtures**
**Relevant ingredients**

CAS No	Components	Quantity
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	31 %
	reaction mass of ethylbenzene and xylene	11.66 %
8050-09-7	Rosin, colophony	6.899 %
141-78-6	ethyl acetate	4.499 %
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	2.76 %
25085-50-1	Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol	1.51 %
128601-23-0	Hydrocarbons, C9, aromatics	1.38 %
1333-86-4	Carbon Black	0.84 %

**Further Information**

Full text of H statements: see section 16.

**4. First-aid measures**
**Description of first aid measures**
**General information**

If unconscious but breathing normally, place in recovery position and seek medical advice.  
 Never give anything by mouth to an unconscious person or a person with cramps.  
 In all cases of doubt, or when symptoms persist, seek medical advice.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 447 Black

Revision date: 12/16/2025

Product code: 5100

Page 3 of 13

#### After contact with skin

Change contaminated clothing.  
Rinse skin with water [or shower].  
If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).  
Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.  
Do NOT induce vomiting.

#### Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

#### Indication of any immediate medical attention and special treatment needed

No information available.

## 5. Fire-fighting measures

#### Extinguishing media

##### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water fog.

##### Unsuitable extinguishing media

High power water jet.

#### Specific hazards arising from the chemical

Combustible. Vapors may form explosive mixtures with air.  
Formation of: Carbon monoxide

#### Special protective equipment and precautions for fire-fighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapors/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

##### General advice

Provide adequate ventilation.  
Wear personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Avoid breathing dust/fume/gas/mist/vapors/spray.

##### For emergency responders

For further specification, refer to section 8 of the SDS.

#### Environmental precautions

Do not allow uncontrolled discharge of product into the environment.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### Methods and material for containment and cleaning up

##### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).  
Treat the recovered material as prescribed in the section on waste disposal.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 4 of 13

**For cleaning up**

- Provide adequate ventilation.
- Clear contaminated areas thoroughly.
- Do not rinse down with water.

**Other information**

- No information available.

**Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment (PPE): see section 8
- Disposal: see section 13

**7. Handling and storage****Precautions for safe handling****Advice on safe handling**

- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

- Take precautionary measures against static discharges.
- Keep away from sources of ignition - No smoking.
- Vapours are heavier than air and will spread at floor level.
- Vapours may form explosive mixtures with air.

**Advice on general occupational hygiene**

- Keep away from food, drink and animal feedingstuffs.
- When using do not eat or drink.
- Wash hands before breaks and after work.
- Avoid contact with skin and eyes.
- Remove contaminated, saturated clothing immediately.
- Do not breathe gas/vapour/aerosol.

**Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

- Keep container tightly closed in a cool, well-ventilated place.
- Keep container dry.
- Keep away from heat. Protect from direct sunlight.

**Hints on joint storage**

- Do not store together with: Oxidizing agents. Strong acid, strong alkalis

**8. Exposure controls/personal protection****Control parameters**

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 5 of 13

**Exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	Category	Origin
1317-65-3	Calcium carbonate (total)	-	10	TWA (8 h)	REL
1317-65-3	Calcium Carbonate Respirable fraction	-	5	TWA (8 h)	REL
1333-86-4	Carbon black (in presence of polycyclic aromatic hydrocarbons (PAHs)) (as PAHs)	-	0.1	TWA (8 h)	REL
1333-86-4	Carbon black (inhalable fraction)	-	3	TWA (8 h)	ACGIH-2025
1333-86-4	Carbon black	-	3.5	TWA (8 h)	REL
64-17-5	Ethanol	1000	1880	STEL (15 min)	ACGIH-2025
141-78-6	Ethyl acetate	400	1400	TWA (8 h)	REL
		400	1400	TWA (8 h)	REL
		400	1440	TWA (8 h)	ACGIH-2025
64-17-5	Ethyl alcohol (Ethanol)	1000	1900	TWA (8 h)	REL
64-17-5	Ethyl alcohol	1000	1900	TWA (8 h)	REL
8050-09-7	Resin acids, as total Resin acids	-	0.001	TWA (8 h)	ACGIH-2025
14807-96-6	Talc (containing no asbestos and less than 1% quartz) (resp)	-	2	TWA (8 h)	REL
14807-96-6	Talc (containing no asbestos) respirable dust	706 mp/m <sup>3</sup>	-	TWA (8 h)	REL
14807-96-6	Talc containing no asbestos fibers (respirable fraction)	-	2	TWA (8 h)	ACGIH-2025

**Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Eye glasses with side protection (EN 166)

**Hand protection**

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber) Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 6 of 13

gas filtering equipment (EN 141), Filter material/medium: A/P2

**9. Physical and chemical properties**
**Information on basic physical and chemical properties**

Physical state:	Liquid
Color:	black
Odor:	characteristic
Odour threshold:	not determined

**Test method**

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	88 °C	
Flammability:	not applicable	
Lower explosion limits:	0,8 vol. %	
Upper explosion limits:	7,7 vol. %	
Flash point:	- 12 °C	DIN 51755
Auto-ignition temperature:	200 °C	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	not determined	
Vapor pressure:	85 hPa	
(at 20 °C)		
Density (at 20 °C):	1,02 - 1,06 g/cm <sup>3</sup>	ISO 2811
Relative vapour density:	not determined	
Particle characteristics:	not determined	

**Other information**
**Information with regard to physical hazard classes**

Explosive properties	not determined
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	not determined

**Other safety characteristics**

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	51,80 %, water: 0,02 %
Solid content:	46 - 50 %
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Viscosity / dynamic:	400 - 600 mPa·s
(at 20 °C)	

**Further Information**

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 7 of 13

No information available.

**10. Stability and reactivity****Reactivity**

No hazardous reaction when handled and stored according to provisions.

**Chemical stability**

Stability: Stable

The product is stable under storage at normal ambient temperatures.

**Possibility of hazardous reactions**

Hazardous reactions: Will not occur

No known hazardous reactions.

**Conditions to avoid**

Keep away from heat.

**Incompatible materials**

No information available.

**Hazardous decomposition products**

Carbon monoxide

**11. Toxicological information****Route(s) of Entry**

No information available.

**Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 5000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 12,5 mg/l

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 8 of 13

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat		
	reaction mass of ethylbenzene and xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
8050-09-7	Rosin, colophony				
	oral	LD50 2800 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
141-78-6	ethyl acetate				
	oral	LD50 5620 mg/kg	Rat		
	dermal	LD50 >20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 50 mg/l	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
128601-23-0	Hydrocarbons, C9, aromatics				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 3160 mg/kg	Rabbit		
1333-86-4	Carbon Black				
	oral	LD50 > 8000 mg/kg	Rat		

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitizing effects**

May cause an allergic skin reaction (Rosin, colophony; Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol)

**Carcinogenic/mutagenic/toxic effects for reproduction**

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 447 Black

Revision date: 12/16/2025

Product code: 5100

Page 9 of 13

Suspected of causing cancer (Carbon Black)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

#### Specific target organ toxicity (STOT) - repeated exposure

May cause damage to organs through prolonged or repeated exposure (reaction mass of ethylbenzene and xylene)

Carcinogenicity (IARC):

Talc not containing asbestos or asbestiform fibres (CAS 14807-96-6) is listed in group 2A. Ethanol in alcoholic beverages (CAS 64-17-5) is listed in group 1. Carbon black (CAS 1333-86-4) is listed in group 2B.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

No information available.

#### Additional information on tests

No information available.

#### Practical experience

No information available.

#### Information on other hazards

##### Endocrine disrupting properties

Endocrine disrupting potential No information available.

#### Further information

There are no data available on the preparation/mixture itself.

## 12. Ecological information

### Ecotoxicity

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 10 of 13

CAS No	Components					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 mg/l	10-100	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	30-100	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss (Rainbow trout)	
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	
8050-09-7	Rosin, colophony					
	Acute algae toxicity	ErC50 mg/l	400-410	72 h	Scenedesmus subspicatus	
	Fish toxicity	NOEC	>1 mg/l	4 d	Danio rerio (zebrafish)	
	Acute bacteria toxicity	EC50 mg/l ( )	>10000	3 h	Activated sludge	
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	3300		Desmodesmus subspicatus	48 h
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	EC50 mg/l ( )	2900		Pseudomonas putida	16 h
128601-23-0	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h		
1333-86-4	Carbon Black					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Brachydanio rerio (Zebrafärbling)	
	Algae toxicity	NOEC mg/l	10000	3 d	Scenedesmus subspicatus	

**Persistence and degradability**

There are no data available on the mixture itself.

**Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Components	Log Pow
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	3,4-5,2
141-78-6	ethyl acetate	0,73

**Mobility in soil**

There are no data available on the mixture itself.

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 11 of 13

**Other adverse effects**

No information available.

**Further information**

There are no data available on the preparation/mixture itself.  
Do not allow to enter into surface water or drains.

**13. Disposal considerations**
**Waste treatment methods**
**Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes.

**Contaminated packaging**

Remove according to the regulations.

**14. Transport information**
**U.S. DOT 49 CFR 172.101**

**UN number or ID number:** UN 1139  
**Transport hazard class(es):** 3  
**Packing group:** II

**Marine transport (IMDG)**

**UN number or ID number:** UN 1139  
**UN proper shipping name:** COATING SOLUTION (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; Hydrocarbons, C9, aromatics), MARINE POLLUTANT

**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Marine pollutant: yes  
Special Provisions: -  
Limited quantity: 5 L  
EmS: F-E, S-E

**Other applicable information (marine transport)**  
E2

**Air transport (ICAO-TI/IATA-DGR)**

**UN number or ID number:** UN 1139  
**UN proper shipping name:** COATING SOLUTION  
**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 1 L  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 447 Black**

Revision date: 12/16/2025

Product code: 5100

Page 12 of 13

**Other applicable information (air transport)**

E2

Passenger-LQ: Y341

**Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: Yes


 Danger releasing substance: trizinc bis(orthophosphate)  
Hydrocarbons, C9, aromatics

**Special precautions for user**

Warning: Flammable liquids

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**15. Regulatory information**
**U.S. Regulations**
**National Inventory TSCA**

Substance/product listed in the following inventories: TSCA

**National regulatory information**

SARA Section 304 CERCLA:

Ethyl acetate (141-78-6): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane (-): Fire hazard, Immediate (acute) health hazard

reaction mass of ethylbenzene and xylene (-): Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Rosin, colophony (8050-09-7): Immediate (acute) health hazard

Ethyl acetate (141-78-6): Fire hazard, Immediate (acute) health hazard

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (-): Fire hazard, Immediate (acute) health hazard

Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol (25085-50-1): Immediate (acute) health hazard

Hydrocarbons, C9, aromatics (128601-23-0): Fire hazard, Immediate (acute) health hazard

Ethanol (64-17-5): Fire hazard

Carbon Black (1333-86-4): Delayed (chronic) health hazard

**State Regulations**
**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

 WARNING: This product can expose you to chemicals including Carbon black (airborne, unbound particles of respirable size) (cancer); Formaldehyde (gas) (cancer), which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

 Directive 2004/42/EC on VOC in 51,8 % (539 g/l)  
paints and varnishes:

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

311362

**16. Other information**
**Hazardous Materials Identification System (HMIS)**

Health: 0

Flammability: 2

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 447 Black

Revision date: 12/16/2025

Product code: 5100

Page 13 of 13

Physical Hazard: 0


#### NFPA Hazard Ratings

Health: 0

Flammability: 2

Reactivity: 0

Unique Hazard:



#### Changes

Revision date: 12/16/2025

Revision No: 2,0

This data sheet contains changes from the previous version in section(s): 2,9,11.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*