

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 1 of 17

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

DINITROL 447 Light Grey

UFI: XJ8J-P4VS-R00U-0F21

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Anti-corrosive coating

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

**Supplier**

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

**1.4. Emergency telephone number:**

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225  
 Skin Irrit. 2; H315  
 Eye Irrit. 2; H319  
 STOT SE 3; H336  
 STOT RE 2; H373  
 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**Regulation (EC) No 1272/2008**

**Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  
 reaction mass of ethylbenzene and xylene  
 ethyl acetate  
 Hydrocarbons, C9, aromatics

**Signal word:** Danger


**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 2 of 17

**Pictograms:**



**Hazard statements**

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe the mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves and eye protection/face protection.
- P403+P235 Store in a well-ventilated place. Keep cool.


**Special labelling**

Restricted to professional users.

**Labelling of packages where the contents do not exceed 125 ml**

**Signal word:** Danger

**Pictograms:**



**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 3 of 17

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			25 - < 30 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	reaction mass of ethylbenzene and xylene			10 - < 15 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
141-78-6	ethyl acetate			5 - < 10 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
128601-23-0	Hydrocarbons, C9, aromatics			1 - < 5 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
7779-90-0	trizinc bis(orthophosphate)			1 - < 5 %
	231-944-3	030-011-00-6	01-2119485044-40	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
13463-67-7	titanium dioxide			< 1 %
	236-675-5		01-2119489379-17	

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	25 - < 30 %
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg		
	905-588-0	reaction mass of ethylbenzene and xylene	10 - < 15 %
	inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4300 mg/kg		
141-78-6	205-500-4	ethyl acetate	5 - < 10 %
	inhalation: LC50 = 50 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 5620 mg/kg		
128601-23-0	918-668-5	Hydrocarbons, C9, aromatics	1 - < 5 %
	dermal: LD50 = > 3160 mg/kg; oral: LD50 = > 2000 mg/kg		
7779-90-0	231-944-3	trizinc bis(orthophosphate)	1 - < 5 %
	inhalation: LC50 = > 5,7 mg/l (dusts or mists); oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1		
13463-67-7	236-675-5	titanium dioxide	< 1 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		

**Further Information**

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are therefore not given, as there is no longer any risk of inhalation of these substances (when handling this

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 4 of 17

mixture).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

If unconscious but breathing normally, place in recovery position and seek medical advice.  
 Never give anything by mouth to an unconscious person or a person with cramps.  
 In all cases of doubt, or when symptoms persist, seek medical advice.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

Change contaminated clothing.  
 Wash with plenty of water/Soap.  
 If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing. In case of eye irritation consult an ophthalmologist.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).  
 Call a physician immediately.  
 Put victim at rest, cover with a blanket and keep warm.  
 Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

Nausea, Dizziness, Headache.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water fog.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.  
 Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

**5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers.

**Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.  
 Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Provide adequate ventilation.  
 Wear personal protection equipment.  
 Avoid contact with skin, eyes and clothes.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 5 of 17

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe the gas/vapour/aerosol.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat. Protect from direct sunlight.

**Hints on joint storage**

Do not store together with: Oxidizing agents. Strong acid, strong alkalis

**7.3. Specific end use(s)**

Anti-corrosive coating

**SECTION 8: Exposure controls/personal protection**

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 6 of 17

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
13463-67-7	Titanium dioxide, total inhalable	-	10		TWA (8 h)	WEL

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 7 of 17

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
<b>DNEL type</b>				
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
reaction mass of ethylbenzene and xylene				
Worker DNEL, long-term		inhalation	systemic	211 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	221 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	442 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day
Worker DNEL, acute		inhalation	local	289 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	14,8 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	734 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	1468 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	734 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	1468 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	734 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
128601-23-0	Hydrocarbons, C9, aromatics			
Worker DNEL, long-term		inhalation	systemic	150 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day
7779-90-0	trizinc bis(orthophosphate)			
Worker DNEL, long-term		inhalation	systemic	5 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,83 mg/kg bw/day

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 8 of 17

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
reaction mass of ethylbenzene and xylene		
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,64 mg/kg
Marine sediment		12,64 mg/kg
Soil		2,31 mg/kg
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		0,20 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg
7779-90-0	trizinc bis(orthophosphate)	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Freshwater sediment		117,8 mg/kg
Marine sediment		56,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,100 mg/l
Soil		35,6 mg/kg

**8.2. Exposure controls**



**Appropriate engineering controls**

Provide adequate ventilation.  
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.  
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Eye glasses with side protection (EN 166)

**Hand protection**

Tested protective gloves must be worn (EN ISO 374):  
 FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.  
 NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.  
 Thickness of the glove material : > 0,12 mm  
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
 Protective gloves have to be replaced at the first sign of deterioration.  
 Protect skin by using skin protective cream.

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 9 of 17

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.  
gas filtering equipment (EN 141),. Filter material/medium: A/P2

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	light grey	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		80 °C
Flammability:		not applicable
Lower explosion limits:		0,8 vol. %
Upper explosion limits:		7,7 vol. %
Flash point:		- 5 °C
Auto-ignition temperature:		200 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		61 hPa
(at 20 °C)		
Density (at 20 °C):		1,04 - 1,08 g/cm <sup>3</sup>
Relative vapour density:		not determined
Particle characteristics:		not determined

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties	
not determined	
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

**Other safety characteristics**

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	52,00 %
Solid content:	46 - 50 %
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 10 of 17

Viscosity / dynamic:  
(at 20 °C)

400 - 600 mPa·s

**Further Information**

No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep away from heat.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Carbon monoxide

**SECTION 11: Toxicological information****11.1. Information on hazard classes****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 5000 mg/kg

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 11 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat		
	reaction mass of ethylbenzene and xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
141-78-6	ethyl acetate				
	oral	LD50 5620 mg/kg	Rat		
	dermal	LD50 >20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 50 mg/l	Rat		
128601-23-0	Hydrocarbons, C9, aromatics				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 3160 mg/kg	Rabbit		
7779-90-0	trizinc bis(orthophosphate)				
	oral	LD50 > 5000 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 > 5,7 mg/l	Rat		
13463-67-7	titanium dioxide				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane)

**STOT-repeated exposure**

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 12 of 17

May cause damage to organs through prolonged or repeated exposure. (reaction mass of ethylbenzene and xylene)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**
**Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information**
**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 mg/l	10-100	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	30-100	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss (Rainbow trout)	
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	3300		Desmodesmus subspicatus	48 h
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	EC50 mg/l ( )	2900		Pseudomonas putida	16 h
128601-23-0	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h		

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	OECD 301F	98%	28	
	Readily biodegradable (according to OECD criteria).			
141-78-6	ethyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28	
	Readily biodegradable (according to OECD criteria).			

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 13 of 17

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	3,4-5,2
141-78-6	ethyl acetate	0,73

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

There are no data available on the preparation/mixture itself.  
Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes.  
List of proposed waste codes/waste designations in accordance with EWC:

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Remove according to the regulations.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

- 14.1. UN number or ID number:** UN 1139
- 14.2. UN proper shipping name:** Coating solution, ENVIRONMENTALLY HAZARDOUS
- 14.3. Transport hazard class(es):** 3
- 14.4. Packing group:** II
- Hazard label: 3



Classification code: F1

### DINITROL 447 Light Grey

Revision: 16.12.2025

Product code: 5101

Page 14 of 17

Special Provisions: 640D  
 Limited quantity: 5 L  
 Transport category: 2  
 Hazard No: 33  
 Tunnel restriction code: D/E

**Other applicable information (land transport)**

E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; Hydrocarbons, C9, aromatics), MARINE POLLUTANT  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Marine pollutant: yes  
 Special Provisions: -  
 Limited quantity: 5 L  
 EmS: F-E, S-E

**Other applicable information (marine transport)**

E2

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 1 L  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**Other applicable information (air transport)**

E2

Passenger-LQ: Y341

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, C9, aromatics  
 trizinc bis(orthophosphate)

**14.6. Special precautions for user**

Warning: Flammable liquids

**14.7. Maritime transport in bulk according to IMO instruments**

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 15 of 17

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes:	52,0 % 540 g/l
Information according to Directive 2012/18/EU (SEVESO III):	E2 Hazardous to the Aquatic Environment
Additional information:	P5c

**Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

**Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  
Hydrocarbons, C9, aromatics

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 2,8,9,11.

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 16 of 17

**Abbreviations and acronyms**

Flam. Liq. 2: Flammable liquids, hazard category 2  
 Flam. Liq. 3: Flammable liquids, hazard category 3  
 Acute Tox. 4: Acute toxicity, hazard category 4  
 Asp. Tox. 1: Aspiration hazard, hazard category 1  
 Skin Irrit. 2: Skin irritation, hazard category 2  
 Eye Irrit. 2: Eye irritation, hazard category 2  
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3  
 STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2  
 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

**DINITROL 447 Light Grey**

Revision: 16.12.2025

Product code: 5101

Page 17 of 17

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*