

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 4479

UFI: PY5C-GMXF-N00Y-864M

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

| | | |
|-------------------------|----------------------|--------------------------------|
| Company name: | DINOL GmbH | |
| Street: | Pyrmonter Strasse 76 | |
| Place: | D-32676 Luegde | |
| Telephone: | + 49 (0) 5281 982980 | Telefax: + 49 (0) 5281 9829860 |
| E-mail: | msds@dinol.com | |
| Contact person: | Labor | |
| Internet: | www.dinol.com | |
| Responsible Department: | msds@dinol.com | |

Supplier

| | |
|---------------|----------------------------------|
| Company name: | Leading Solvent Supplies Limited |
| Street: | Marston Business Park, Rudgate |
| Place: | GB Tockwith, York YO26 7QF |
| E-mail: | enquiries@leading-solvents.co.uk |
| Internet: | www.leading-solvents.co.uk |

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Warning

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 2 of 12

H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P243 Take action to prevent static discharges.
 P280 Wear protective gloves and eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Special labelling

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml
Signal word: Warning

Pictograms:

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|---------|---|--------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | 45 - < 50 % |
| | 919-857-5 | | 01-2119463258-33 | |
| | Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066 | | | |
| 64-17-5 | ethanol, ethyl alcohol | | | 1 - < 5 % |
| | 200-578-6 | 603-002-00-5 | 01-2120063206-63 | |
| | Flam. Liq. 2; H225 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|---------|--|---|-------------|
| | Specific Conc. Limits, M-factors and ATE | | |
| | 919-857-5 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 45 - < 50 % |
| | inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg | | |
| 64-17-5 | 200-578-6 | ethanol, ethyl alcohol | 1 - < 5 % |
| | inhalation: LC50 = 20000 mg/l (vapours); oral: LD50 = 7060 mg/kg | | |

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 3 of 12

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice.
 Never give anything by mouth to an unconscious person or a person with cramps.
 In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.
 Wash with plenty of water/Soap.
 If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
 Call a physician immediately.
 Put victim at rest, cover with a blanket and keep warm.
 Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.
 Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.
 Wear personal protection equipment.
 Avoid contact with skin, eyes and clothes.
 Avoid breathing dust/fume/gas/mist/vapours/spray.

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 4 of 12

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal .

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient , the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges .

Keep away from sources of ignition - No smoking.

Vapours are heavier than air and will spread at floor level .

Vapours may form explosive mixtures with air .

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work .

Avoid contact with skin and eyes .

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 5 of 12

7.3. Specific end use(s)

Anti-corrosive coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|---------|-----------|------|-------------------|-----------|-----------|--------|
| 64-17-5 | Ethanol | 1000 | 1920 | | TWA (8 h) | WEL |

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|---|------------------------|----------------|----------|------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | |
| Consumer DNEL, long-term | | oral | systemic | 125 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | systemic | 208 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | systemic | 125 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 871 mg/m ³ |
| Consumer DNEL, long-term | | inhalation | systemic | 185 mg/m ³ |
| 64-17-5 | ethanol, ethyl alcohol | | | |
| Worker DNEL, long-term | | inhalation | systemic | 950 mg/m ³ |
| Worker DNEL, acute | | inhalation | local | 1900 mg/m ³ |
| Worker DNEL, long-term | | dermal | systemic | 343 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 114 mg/m ³ |
| Consumer DNEL, acute | | inhalation | local | 950 mg/m ³ |
| Consumer DNEL, long-term | | dermal | systemic | 206 mg/kg bw/day |
| Consumer DNEL, long-term | | oral | systemic | 87 mg/kg bw/day |

PNEC values

| CAS No | Substance | Value |
|--|------------------------|------------|
| Environmental compartment | | |
| 64-17-5 | ethanol, ethyl alcohol | |
| Freshwater | | 0,96 mg/l |
| Marine water | | 0,79 mg/l |
| Freshwater sediment | | 3,6 mg/kg |
| Marine sediment | | 2,9 mg/kg |
| Secondary poisoning | | 0,72 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 580 mg/l |
| Soil | | 0,63 mg/kg |

8.2. Exposure controls



DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 6 of 12

Appropriate engineering controls

Provide adequate ventilation.
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):
 FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.
 NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.
 Thickness of the glove material : > 0,12 mm
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
 Protective gloves have to be replaced at the first sign of deterioration.
 Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
 gas filtering equipment (EN 141),. Filter material/medium: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|------------------|----------------|
| Physical state: | Liquid |
| Colour: | black |
| Odour: | characteristic |
| Odour threshold: | not determined |

| | Test method |
|---|--|
| Melting point/freezing point: | not determined |
| Boiling point or initial boiling point and boiling range: | 154 - 193 °C |
| Flammability: | not applicable |
| Lower explosion limits: | 0,7 vol. % |
| Upper explosion limits: | 6,0 vol. % |
| Flash point: | 36 °C |
| Auto-ignition temperature: | > 200 °C |
| Decomposition temperature: | not determined |
| pH-Value: | not determined |
| Water solubility: | The study does not need to be conducted because the substance is known to be insoluble in water. |
| Solubility in other solvents | |
| not determined | |
| Partition coefficient n-octanol/water: | not determined |
| Vapour pressure: | 3 hPa |
| (at 20 °C) | |
| Vapour pressure: | 13 hPa |
| (at 50 °C) | |
| Density (at 20 °C): | 1,10 - 1,14 g/cm³ |

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 7 of 12

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

31,4 %

Solid content:

66 - 70 %

Viscosity / dynamic:

2200 mPa·s

(at 20 °C)

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 8 of 12

| CAS No | Chemical name | | | | |
|---------|---|-------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | |
| | oral | LD50 > 5000 mg/kg | Rat | | |
| | dermal | LD50 > 5000 mg/kg | Rabbit | | |
| | inhalation (4 h) vapour | LC50 > 5000 mg/l | Rat | | |
| 64-17-5 | ethanol, ethyl alcohol | | | | |
| | oral | LD50 7060 mg/kg | Rat | | |
| | inhalation (4 h) vapour | LC50 20000 mg/l | Rat | | |

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.
 Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.
 Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
 Carcinogenicity: Based on available data, the classification criteria are not met.
 Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C 11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 9 of 12

12.2. Persistence and degradability

There are no data available on the mixture itself.

| CAS No | Chemical name | | | |
|--------|---|-------|---|--------|
| | Method | Value | d | Source |
| | Evaluation | | | |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | |
| | | 80% | | |
| | Readily biodegradable (according to OECD criteria). | | | |

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.
List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number or ID number:** UN 1139
- 14.2. UN proper shipping name:** COATING SOLUTION
- 14.3. Transport hazard class(es):** 3
- 14.4. Packing group:** III

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 10 of 12

Hazard label: 3



Classification code: F1
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 30
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Marine pollutant: no
 Special Provisions: 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 11 of 12

| | |
|------------------------------------|-------|
| IATA-max. quantity - Passenger: | 60 L |
| IATA-packing instructions - Cargo: | 366 |
| IATA-max. quantity - Cargo: | 220 L |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

| | |
|---|-----------------------|
| Directive 2004/42/EC on VOC in paints and varnishes: | 31,84 % 356,6 g/l |
| Information according to Directive 2012/18/EU (SEVESO III): | P5c FLAMMABLE LIQUIDS |

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

666728

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 8.

DINITROL 4479

Revision: 20.01.2026

Product code: 21671

Page 12 of 12

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
 Flam. Liq. 3: Flammable liquids, hazard category 3
 Asp. Tox. 1: Aspiration hazard, hazard category 1
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method

| Classification | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data |
| STOT SE 3; H336 | Calculation method |

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)