

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 460

UFI: DEH2-88K4-F00G-2G14

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

Supplier

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
 Skin Irrit. 2; H315
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 2 of 10

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapour.
- P273 Avoid release to the environment.
- P280 Wear protective gloves and eye protection/face protection.
- P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

Hazard statements

H412

2.3. Other hazards

Avoid release to the environment.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
	Hydrocarbons, C6-C7, n-alkanes,Isoalkanes, cyclic, <5% n-hexane	15 - < 20 %
	921-024-6	01-2119475514-35
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	921-024-6	Hydrocarbons, C6-C7, n-alkanes,Isoalkanes, cyclic, <5% n-hexane	15 - < 20 %
		inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = >3920 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. Call a doctor if you feel unwell.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 3 of 10

In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Call a physician immediately.
Do NOT induce vomiting.
Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂)
Foam
Extinguishing powder
Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Formation of: Pyrolysis products, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.
Remove all sources of ignition.
Special danger of slipping by leaking/spilling product.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 4 of 10

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C6-C7, n-alkanes, Isoalkanes, cyclic, <5% n-hexane			
	Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	2035 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	608 mg/m ³

8.2. Exposure controls

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 5 of 10



Appropriate engineering controls

Provide adequate ventilation.
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Recommended glove articles :
 FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.
 NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
 Protective gloves have to be replaced at the first sign of deterioration.
 Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing.

Respiratory protection

Use appropriate respiratory protection.
 Suitable respiratory protection apparatus: Filtering device (full mask or mouthpiece) with filter: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	black
Odour:	like: Gasoline
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	<0 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	>20,5 mm ² /s
Water solubility:	not determined
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	85 hPa

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 6 of 10

Density (at 20 °C):	1,45 g/cm ³ DIN 51757
Bulk density:	not applicable
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	not determined
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	not determined

Other safety characteristics

Solvent content:	not determined
Solid content:	not determined
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Viscosity / dynamic:	not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

In use may form flammable/explosive vapour-air mixture.
 Reacts with : Oxidising agent

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Gases/vapours, flammable
 Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 7 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, Isoalkanes, cyclic, <5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >3920 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards
Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information
12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 8 of 10

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.
List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number or ID number:** UN 1133
- 14.2. UN proper shipping name:** Adhesives
- 14.3. Transport hazard class(es):** 3
- 14.4. Packing group:** III
- Hazard label: 3



- Classification code: F1
- Special Provisions: 640H
- Limited quantity: 5 L
- Transport category: 3
- Hazard No: 33
- Tunnel restriction code: D/E

Other applicable information (land transport)

E1

Marine transport (IMDG)

- 14.1. UN number or ID number:** UN 1133
- 14.2. UN proper shipping name:** Adhesives
- 14.3. Transport hazard class(es):** 3
- 14.4. Packing group:** III

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 9 of 10

Hazard label: 3



Special Provisions: 223, 955

Limited quantity: 5 L

EmS: F-E, S-D

Other applicable information (marine transport)

E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1133

14.2. UN proper shipping name: Adhesives

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Special Provisions: A3

Limited quantity Passenger: 10 L

IATA-packing instructions - Passenger: 355

IATA-max. quantity - Passenger: 60 L

IATA-packing instructions - Cargo: 366

IATA-max. quantity - Cargo: 220 L

Other applicable information (air transport)

E1

Passenger-LQ: Y344

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Marine pollutant: no

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2004/42/EC on VOC in 15,0 %

paints and varnishes: 218,0 g/l

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

DINITROL 460

Revision: 29.04.2026

Product code: 90460

Page 10 of 10

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Abbreviations and acronyms

- Flam. Liq. 2: Flammable liquids, hazard category 2
- Asp. Tox. 1: Aspiration hazard, hazard category 1
- Skin Irrit. 2: Skin irritation, hazard category 2
- STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
- Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
- Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)