

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 1 of 12

**1. Identification**
**Product identifier**

DINITROL 4941/CAR Spray

**Recommended use of the chemical and restrictions on use**
**Use of the substance/mixture**

Anti-corrosive coating

**Uses advised against**

No further relevant information available.

**Details of the supplier of the safety data sheet**
**Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

**Supplier**


Company name:	DINOL U.S. Inc.	
Street:	8500 Cotter Street, Lewis Center	
Place:	USA-43035 Ohio	
Telephone:	740-548-1656	Telefax: 740-548-1657
E-mail:	info@dinolus.com	
Internet:	www.dinol.com	

**Emergency phone number:** 3E Company Emergency +1-866-404-4230

**2. Hazard(s) identification**
**Classification of the chemical**
**29 CFR Part 1910.1200**

Flammable aerosols: Category 1  
 Gases under pressure: Compressed gas  
 Carcinogenicity: Category 1B  
 Germ cell mutagenicity: Category 1B  
 Serious eye damage/eye irritation: Category 2A  
 Specific target organ toxicity single exposure: Category 3 (narcotic effects)

**Label elements**
**29 CFR Part 1910.1200**
**Signal word:** Danger

**Pictograms:**

**Hazard statements**

Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated  
 Causes serious eye irritation

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 4941/CAR Spray

Revision date: 04/30/2026

Product code: 21707

Page 2 of 12

May cause drowsiness or dizziness

May cause genetic defects

May cause cancer

#### Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Hazards not otherwise classified

Endocrine disrupting properties: butanone; ethyl methyl ketone.

No information available.

### 3. Composition/information on ingredients

#### Mixtures

##### Relevant ingredients

CAS No	Components	Quantity
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	24.9 %
78-93-3	butanone; ethyl methyl ketone	24.9 %
74-98-6	propane	24.9 %
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics	4.9 %
128601-23-0	Hydrocarbons, C9, aromatics	2.9 %
	Hydrocarbons, C6-C7, n-alkanes, Isoalkanes, cyclic, <5% n-hexane	2.9 %

#### Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w)

DMSO extract (IP 346)).

### 4. First-aid measures

#### Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

##### After inhalation

Remove casualty to fresh air and keep warm and at rest.

##### After contact with skin

Change contaminated clothing.

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 4941/CAR Spray

Revision date: 04/30/2026

Product code: 21707

Page 3 of 12

Wash with plenty of water/Soap.

If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

#### Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### Indication of any immediate medical attention and special treatment needed

No information available.

## 5. Fire-fighting measures

#### Extinguishing media

##### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder. Water fog.

##### Unsuitable extinguishing media

High power water jet.

#### Specific hazards arising from the chemical

No further relevant information available.

#### Special protective equipment and precautions for fire-fighters

Use appropriate respiratory protection.

#### Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapors/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

##### General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapors/spray.

##### For emergency responders

For further specification, refer to section 8 of the SDS.

#### Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### Methods and material for containment and cleaning up

##### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

##### For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 4 of 12

Do not rinse down with water.

**Other information**

No information available.

**Reference to other sections**

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

**7. Handling and storage****Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Further information on handling**

No further relevant information available.

**Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Not required.

**Further information on storage conditions**

Keep container tightly closed.

**8. Exposure controls/personal protection****Control parameters**

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 5 of 12

**Exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	Category	Origin
78-93-3	2-Butanone (Methyl ethyl ketone)	200	590	TWA (8 h)	REL
78-93-3	2-Butanone	200	590	TWA (8 h)	REL
		300	885	STEL (15 min)	REL
75-28-5	Butane: isobutane	1000	2370	STEL (15 min)	ACGIH-2025
106-97-8	Butane: n-butane	1000	2370	STEL (15 min)	ACGIH-2025
75-28-5	Isobutane	800	1900	TWA (8 h)	REL
78-93-3	Methyl ethyl ketone	75		TWA (8 h)	ACGIH-2025
		150		STEL (15 min)	ACGIH-2025
106-97-8	n-Butane	800	1900	TWA (8 h)	REL
74-98-6	Propane	1000	1800	TWA (8 h)	REL
		1000	1800	TWA (8 h)	REL
		-	-	Asphyxiant	ACGIH-2025

**Biological Exposure Indices (BEI-ACGIH)**

CAS No	Substance	Determinant	Value	Test material	Sampling time
78-93-3	METHYL ETHYL KETONE	Methyl ethyl ketone	2 mg/L	urine	End of shift

**Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Eye glasses with side protection (DIN EN 166)

**Hand protection**

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

Thickness of the glove material : > 0,12 mm

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A

short-term Filter material/medium : A1/P1

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 6 of 12

long-term Filter material/medium : A1/P2

**9. Physical and chemical properties**
**Information on basic physical and chemical properties**

Physical state:	Aerosol
Color:	black
Odor:	characteristic
Odour threshold:	not determined

**Test method**

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	- 44,5 °C	
Flammability:	not determined	
Lower explosion limits:	0,9 vol. %	
Upper explosion limits:	11,5 vol. %	
Flash point:	< - 97 °C	DIN 53213
Auto-ignition temperature:	> 200 °C	
Decomposition temperature:	not determined	
pH-Value:	The study does not need to be conducted because the substance is known to be insoluble in water. not determined	
Viscosity / kinematic:	not determined	
Water solubility:	not applicable	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	not determined	
Vapor pressure:	3500 hPa	
(at 20 °C)		
Vapor pressure:	370 hPa	
(at 50 °C)		
Density (at 20 °C):	0,8 g/cm <sup>3</sup>	DIN 51757
Relative vapour density:	not determined	
Particle characteristics:	not applicable	

**Other information**
**Information with regard to physical hazard classes**

Explosive properties	not determined
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	not determined
Gas:	not determined
Oxidizing properties	not determined

**Other safety characteristics**

Solvent content:	63,82 %
Solid content:	36,2 %
Softening point:	not determined
Viscosity / dynamic:	not determined

**Further Information**

No information available.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 7 of 12

**10. Stability and reactivity****Reactivity**

No hazardous reaction when handled and stored according to provisions.

**Chemical stability**

Stability: Stable

The product is stable under storage at normal ambient temperatures.

**Possibility of hazardous reactions**

Hazardous reactions: Will not occur

No known hazardous reactions.

**Conditions to avoid**

No further relevant information available.

**Incompatible materials**

No information available.

**Hazardous decomposition products**

Carbon monoxide

**11. Toxicological information****Route(s) of Entry**

No information available.

**Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation gas) &gt; 20000 ppm

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 8 of 12

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat		
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 3300 mg/kg	Rat		
	dermal	LD50 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 12 mg/l	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
128601-23-0	Hydrocarbons, C9, aromatics				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 3160 mg/kg	Rabbit		
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >3920 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat		

**Irritation and corrosivity**

Serious eye damage/eye irritation: Causes serious eye irritation

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**Sensitizing effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

May cause cancer (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics)

May cause genetic defects (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics)

Reproductive toxicity: Based on available data, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure**

May cause drowsiness or dizziness (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; butanone; ethyl methyl ketone)

**Specific target organ toxicity (STOT) - repeated exposure**

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA): No ingredient of this mixture is listed.

Carcinogenicity (IARC): No ingredient of this mixture is listed.

Carcinogenicity (NTP): No ingredient of this mixture is listed.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 9 of 12

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**Information on other hazards**
**Endocrine disrupting properties**

Endocrine disrupting properties: butanone; ethyl methyl ketone.

**Further information**

There are no data available on the preparation/mixture itself.

**12. Ecological information**
**Persistence and degradability**

There are no data available on the mixture itself.

**Bioaccumulative potential**

There are no data available on the mixture itself.

**Mobility in soil**

There are no data available on the mixture itself.

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other adverse effects**

No information available.

**Further information**

There are no data available on the mixture itself.

**13. Disposal considerations**
**Waste treatment methods**
**Disposal recommendations**

 Dispose of waste according to applicable legislation.  
 Do not mix with other wastes.

**Contaminated packaging**

Dispose according to legislation.

**14. Transport information**
**U.S. DOT 49 CFR 172.101**
**UN number or ID number:**

UN 1950

**Proper shipping name:**

AEROSOLS

**Transport hazard class(es):**

2.1

Hazard label:

2.1


**Marine transport (IMDG)**

**Safety Data Sheet**


according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**


Revision date: 04/30/2026

Product code: 21707

Page 10 of 12

<b><u>UN number or ID number:</u></b>	UN 1950
<b><u>UN proper shipping name:</u></b>	AEROSOLS
<b><u>Transport hazard class(es):</u></b>	2.1
<b><u>Packing group:</u></b>	-
Hazard label:	2.1
	
Marine pollutant:	no
Special Provisions:	63, 190, 277, 327, 344, 381, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

<b><u>UN number or ID number:</u></b>	UN 1950
<b><u>UN proper shipping name:</u></b>	AEROSOLS, FLAMMABLE
<b><u>Transport hazard class(es):</u></b>	2.1
<b><u>Packing group:</u></b>	-
Hazard label:	2.1
	

Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**Special precautions for user**

Warning : gas

**Other applicable information**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Category C, Clear of living quarters.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 11 of 12

**15. Regulatory information**
**U.S. Regulations**
**National Inventory TSCA**

Substance/product listed in the following inventories: TSCA

**National regulatory information**
**SARA Section 304 CERCLA:**

Methyl ethyl ketone (78-93-3): Reportable quantity = 5,000 (2270) lbs. (kg)

**SARA Section 311/312 Hazards:**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics (-): Fire hazard, Immediate (acute) health hazard

Methyl ethyl ketone (78-93-3): Fire hazard, Immediate (acute) health hazard

Propane (74-98-6): Fire hazard, Sudden release of pressure

Isobutane (75-28-5): Fire hazard, Sudden release of pressure

Butane (106-97-8): Fire hazard, Sudden release of pressure

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics (-): Fire hazard, Delayed (chronic) health hazard, Immediate (acute) health hazard

Hydrocarbons, C9, aromatics (128601-23-0): Fire hazard, Immediate (acute) health hazard

Hydrocarbons, C6-C7, n-alkanes, Isoalkanes, cyclic, &lt;5% n-hexane (-): Fire hazard, Immediate (acute) health hazard

**Clean Air Act Section 112(r):**

Propane (74-98-6): Threshold quantities = 10,000 lbs.

Isobutane (75-28-5): Threshold quantities = 10,000 lbs.

Butane (106-97-8): Threshold quantities = 10,000 lbs.

**Clean Air Act Section 112(b):**

Methyl ethyl ketone (78-93-3)

**State Regulations**
**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Directive 2004/42/EC on VOC in	63,82 %
paints and varnishes:	510,5 g/l

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

602306

**16. Other information**
**Hazardous Materials Identification System (HMIS)**

Health:	2
Flammability:	4
Physical Hazard:	3

**NFPA Hazard Ratings**

Health:	2
Flammability:	4
Reactivity:	3
Unique Hazard:	none


**Changes**

Revision date:	04/30/2026
Revision No:	1,8

This data sheet contains changes from the previous version in section(s): 2.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4941/CAR Spray**

Revision date: 04/30/2026

Product code: 21707

Page 12 of 12

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

**Other data**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet contains only safety-related information and does not replace product information or product specifications.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*