

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

DINITROL 4941 / CAR

UFI: K57G-5SKE-F50K-67G2

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Anti-corrosive coating

**Uses advised against**

No further relevant information available.

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

**Supplier**

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

**1.4. Emergency telephone number:**

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226  
 STOT SE 3; H336  
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**Regulation (EC) No 1272/2008**

**Hazard components for labelling**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics  
 Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified  
 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Signal word:** Warning

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 2 of 14

**Pictograms:**



**Hazard statements**

- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P243 Take action to prevent static discharges.
- P280 Wear protective gloves and eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

**Special labelling**

Restricted to professional users.

**Labelling of packages where the contents do not exceed 125 ml**

**Signal word:** Warning

**Pictograms:**



**Hazard statements**

H412

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 3 of 14

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			20 - < 25 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified			10 - < 15 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			5 - < 10 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304			
108-32-7	propylene carbonate			1 - < 5 %
	203-572-1	607-194-00-1	01-2119537232-48	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	20 - < 25 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = 5000 mg/kg; oral: LD50 = 4951 mg/kg	
	918-668-5	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	10 - < 15 %
		inhalation: LC50 = >6193 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = 3492 mg/kg	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	5 - < 10 %
		dermal: LD50 = >3000 mg/kg; oral: LD50 = > 5000 mg/kg	
108-32-7	203-572-1	propylene carbonate	1 - < 5 %
		dermal: LD50 = > 20000 mg/kg; oral: LD50 = 33520 mg/kg	

**Further Information**

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 4 of 14

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).  
Do NOT induce vomiting.  
Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.

**4.2. Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

In case of fire, use sand, extinguishing powder or alcohol resistant foam.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Gases/vapours, toxic

**5.3. Advice for firefighters**

Wear respiratory protection.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Provide adequate ventilation.  
Wear personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).  
Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.  
Clear contaminated areas thoroughly.

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 5 of 14

Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations. Use only in well-ventilated areas.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

No special measures are necessary.

**Hints on joint storage**

Not required.

**Further information on storage conditions**

Keep container tightly closed.

**7.3. Specific end use(s)**

Not required.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 6 of 14

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Worker DNEL, long-term	inhalation	systemic	871 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	185 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	125 mg/kg bw/day
	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified		
Consumer DNEL, long-term	oral	systemic	11 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	11 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	150 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	systemic	32 mg/m <sup>3</sup>
108-32-7	propylene carbonate		
Worker DNEL, long-term	inhalation	systemic	70,56 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	20 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	17,4 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	10 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	10 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	10 mg/kg bw/day

**PNEC values**

CAS No	Substance	
Environmental compartment	Value	
108-32-7	propylene carbonate	
Freshwater	0,9 mg/l	
Marine water	0,9 mg/l	
Micro-organisms in sewage treatment plants (STP)	7400 mg/l	
Soil	0,81 mg/kg	

**8.2. Exposure controls**



**Appropriate engineering controls**

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Eye glasses with side protection (EN 166)

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 7 of 14

**Hand protection**

Recommended glove articles :  
 FKM (fluoro rubber), Breakthrough time:: 480 min.  
 NBR (Nitrile rubber), Breakthrough time:: 480 min.  
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
 Protective gloves have to be replaced at the first sign of deterioration.  
 Protect skin by using skin protective cream.

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.  
 gas filtering equipment (EN 141),. Filter material/medium: A

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	black
Odour:	characteristic
Odour threshold:	not determined

	<b>Test method</b>
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	165 - 181 °C
Flammability:	not determined
Lower explosion limits:	0,8 vol. %
Upper explosion limits:	6 vol. %
Flash point:	36 °C DIN 53213
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	> 20,5 mm <sup>2</sup> /s
Water solubility:	not applicable
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	5 hPa
(at 20 °C)	
Vapour pressure:	30 hPa
(at 50 °C)	
Density (at 20 °C):	1,01 - 1,05 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not applicable

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties	
not determined	
Sustained combustibility:	No data available
Oxidizing properties	
not determined	

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 8 of 14

**Other safety characteristics**

Solvent content:	org. Lösemittel 37,5 %
	Wassergehalt 0,1 %
Solid content:	58,5 - 63,5 %
Softening point:	not determined
Viscosity / dynamic: (at 20 °C)	1400 - 3500 mPa·s

**Further Information**

No information available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No further relevant information available.

**10.2. Chemical stability**

No known hazardous decomposition products.

**10.3. Possibility of hazardous reactions**

No known hazardous decomposition products.

**10.4. Conditions to avoid**

No further relevant information available.

**10.5. Incompatible materials**

No further relevant information available.

**10.6. Hazardous decomposition products**

Carbon monoxide

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified				
	oral	LD50 3492 mg/kg	Rat		
	dermal	LD50 >3160 mg/kg	Rabbit		
	inhalation vapour	LC50 >6193 mg/l	Rat		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
108-32-7	propylene carbonate				
	oral	LD50 33520 mg/kg	Rat	GESTIS	
	dermal	LD50 > 20000 mg/kg	Rabbit	GESTIS	

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No information available.

**Specific effects in experiment on an animal**

No information available.

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 10 of 14

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-32-7	propylene carbonate					
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna (Big water flea)		

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
108-32-7	propylene carbonate				
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	83,5-87,7 %	29		
	Readily biodegradable (according to OECD criteria).				

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
108-32-7	propylene carbonate	-0,41

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No further relevant information available.

**Further information**

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 11 of 14

**13.1. Waste treatment methods**

**Disposal recommendations**

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**Contaminated packaging**

Dispose of waste according to applicable legislation.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 Transport category: 3  
 Hazard No: 30  
 Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** Coating solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L  
 Excepted quantity: E1

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3


**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 12 of 14

**14.4. Packing group:** III  
**Hazard label:** 3



Marine pollutant: no  
 Special Provisions: 955  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
**Hazard label:** 3



Special Provisions: A3  
 Limited quantity Passenger: 10 L  
 Passenger LQ: Y344  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 355  
 IATA-max. quantity - Passenger: 60 L  
 IATA-packing instructions - Cargo: 366  
 IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**Other applicable information**

Transport classification ADR/IMDG is based on packaging >30ltr(IMDG), >450ltr(ADR).  
 For other packaging until different classification can apply.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 37,86 %  
 390,0 g/l  
 Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

Observe in addition any national regulations!

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 13 of 14

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

**Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

55220

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 16.

**Abbreviations and acronyms**

- Flam. Liq. 3: Flammable liquids, hazard category 3
- Asp. Tox. 1: Aspiration hazard, hazard category 1
- Eye Irrit. 2: Eye irritation, hazard category 2
- STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
- Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
- Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

**DINITROL 4941 / CAR**

Revision: 16.01.2026

Product code: 20091

Page 14 of 14

EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet contains only safety-related information and does not replace product information or product specifications.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*