

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 6090

UFI: S4VE-W0UF-800Q-VQ27

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Bodyfiller/stopper

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

Supplier

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

1.4. Emergency telephone number: Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

- Flam. Liq. 3; H226
- Repr. 2; H361d
- Skin Irrit. 2; H315
- Eye Irrit. 2; H319
- Skin Sens. 1; H317
- STOT SE 3; H335
- STOT RE 1; H372
- Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

- styrene
- Hydrocarbons, C9, aromatics
- Silicon dioxide
- maleic anhydride

Signal word: Danger

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 2 of 14

Pictograms:

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

Hazard statements

H317-H361d-H372-H412

Precautionary statements

P260-P280

2.3. Other hazards

Endocrine disrupting properties: styrene.
No information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 3 of 14

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
100-42-5	styrene			20 - < 25 %
	202-851-5	601-026-00-0	01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412			
128601-23-0	Hydrocarbons, C9, aromatics			1 - < 5 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
14808-60-7	Silicon dioxide			1 - < 5 %
	238-878-4			
	STOT RE 1; H372			
108-31-6	maleic anhydride			< 0.1 %
	203-571-6	607-096-00-9	01-2119472428-31	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1A, STOT RE 1; H302 H314 H318 H334 H317 H372 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
100-42-5	202-851-5	styrene	20 - < 25 %
	inhalation: LC50 = 11,8 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = > 5000 mg/kg		
128601-23-0	918-668-5	Hydrocarbons, C9, aromatics	1 - < 5 %
	dermal: LD50 = > 3160 mg/kg; oral: LD50 = > 2000 mg/kg		
108-31-6	203-571-6	maleic anhydride	< 0.1 %
	dermal: LD50 = 2620 mg/kg; oral: LD50 = 1090 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100		

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

After inhalation

Provide fresh air. In case of irregular breathing or respiratory arrest provide artificial respiration. If unconscious but breathing normally, place in recovery position and seek medical advice. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 4 of 14

physician immediately. Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 5 of 14

SECTION 7: Handling and storage
7.1. Precautions for safe handling
Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place. Keep container dry.

Protect from direct sunlight.

storage temperature: 15 - 25 °C

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7429-90-5	Aluminium metal, inhalable dust	-	10		TWA (8 h)	WEL
108-31-6	Maleic anhydride	-	1		TWA (8 h)	WEL
		-	3		STEL (15 min)	WEL
100-42-5	Styrene	100	430		TWA (8 h)	WEL
		250	1080		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 6 of 14

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
100-42-5	styrene			
Worker DNEL, acute		inhalation	local	289 mg/m ³
Worker DNEL, long-term		inhalation	systemic	306 mg/m ³
Worker DNEL, long-term		inhalation	local	85 mg/m ³
Worker DNEL, long-term		dermal	local	406 mg/person/day
Consumer DNEL, acute		inhalation	local	182,75 mg/m ³
Consumer DNEL, acute		inhalation	systemic	174,25 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	10,2 mg/m ³
Consumer DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2,1 mg/kg bw/day
7429-90-5	aluminium powder (stabilised)			
Worker DNEL, long-term		inhalation	systemic	3,72 mg/m ³
Worker DNEL, long-term		inhalation	local	3,72 mg/m ³
Consumer DNEL, long-term		oral	systemic	3,95 mg/kg bw/day
128601-23-0	Hydrocarbons, C9, aromatics			
Worker DNEL, long-term		inhalation	systemic	150 mg/m ³
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m ³
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day

PNEC values

CAS No	Substance	Value
100-42-5	styrene	
	Environmental compartment	
	Freshwater	0,028 mg/l
	Marine water	0,014 mg/l
	Freshwater sediment	0,614 mg/kg
	Marine sediment	0,307 mg/kg
	Micro-organisms in sewage treatment plants (STP)	5 mg/l
	Soil	0,2 mg/kg
7429-90-5	aluminium powder (stabilised)	
	Freshwater	0,0749 mg/l
	Micro-organisms in sewage treatment plants (STP)	20 mg/l

8.2. Exposure controls

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 7 of 14



Appropriate engineering controls

Provide adequate ventilation.
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):
 FKM (fluoro rubber), Breakthrough time:: 480 min.
 NBR (Nitrile rubber), Breakthrough time:: 30 min.
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
 Protective gloves have to be replaced at the first sign of deterioration.
 Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
 gas filtering equipment (EN 141)., Filter material/medium: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	silver grey
Odour:	characteristic
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	145 °C
Flammability:	not applicable
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	8,9 vol. %
Flash point:	31 °C DIN 51755
Auto-ignition temperature:	480 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 8 of 14

Vapour pressure: (at 20 °C)	6,7 hPa
Density (at 20 °C):	1,45 g/cm ³ ISO 2811
Relative vapour density:	not determined
Particle characteristics:	not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	not determined
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	not determined

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	<3 % (ADR/RID)
Solvent content:	20,8 %
Solid content:	79,2 %
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Viscosity / dynamic: (at 20 °C)	80000 - 90000 mPa·s

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

In case of warming: Danger of polymerisation

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
100-42-5	styrene				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 11,8 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
128601-23-0	Hydrocarbons, C9, aromatics				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 3160 mg/kg	Rabbit		
108-31-6	maleic anhydride				
	oral	LD50 1090 mg/kg	Rat		
	dermal	LD50 2620 mg/kg	Rabbit		

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (maleic anhydride)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (styrene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (styrene)

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (styrene)

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards
Endocrine disrupting properties

Endocrine disrupting properties: styrene.

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information
12.1. Toxicity

Harmful to aquatic life with long lasting effects.

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
100-42-5	styrene					
	Acute fish toxicity	LC50 mg/l	4,02	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	4,9 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	4,7 mg/l	48 h	Daphnia magna (Big water flea)	
	Fish toxicity	NOEC mg/l	1,01	21 d	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	EC50 ()	500 mg/l	0,5 h		
128601-23-0	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h		

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
100-42-5	styrene			
		70,9%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-42-5	styrene	2,96

BCF

CAS No	Chemical name	BCF	Species	Source
100-42-5	styrene	74		

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations
13.1. Waste treatment methods

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 11 of 14

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 640E
 Limited quantity: 5 L
 Transport category: 3
 Hazard No: 30
 Tunnel restriction code: D/E

Other applicable information (land transport)

E1

No good of class 3 according to ADR/RID chapter 2.2.3.1.5.

Marine transport (IMDG)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Marine pollutant: no
 Special Provisions: 223, 955
 Limited quantity: 5 L
 EmS: F-E, S-E

Other applicable information (marine transport)

E1

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 12 of 14

Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.

Air transport (ICAO-TI/IATA-DGR)

- 14.1. UN number or ID number:** UN 1866
- 14.2. UN proper shipping name:** Resin solution
- 14.3. Transport hazard class(es):** 3
- 14.4. Packing group:** III
- Hazard label: 3



- Special Provisions: A3
- Limited quantity Passenger: 10 L
- IATA-packing instructions - Passenger: 355
- IATA-max. quantity - Passenger: 60 L
- IATA-packing instructions - Cargo: 366
- IATA-max. quantity - Cargo: 220 L

Other applicable information (air transport)

- E1
- Passenger-LQ: Y344

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 20,8 % (< 250 g/l)

Subcategory according to Directive 2004/42/EC: Bodyfiller/stopper - All types, VOC limit value: 250 g/l

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 13 of 14

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 9,11,16.

Abbreviations and acronyms

Flam. Liq. 3: Flammable liquids, hazard category 3

Acute Tox. 4: Acute toxicity, hazard category 4

Asp. Tox. 1: Aspiration hazard, hazard category 1

Skin Corr. 1B: Skin corrosion, sub-category 1B

Skin Irrit. 2: Skin irritation, hazard category 2

Eye Dam. 1: Serious eye damage, hazard category 1

Eye Irrit. 2: Eye irritation, hazard category 2

Resp. Sens. 1: Respiratory sensitisation, hazard category 1

Skin Sens. 1: Skin sensitisation, hazard category 1

Skin Sens. 1A: Skin sensitisation, hazard category 1A

Repr. 2: Reproductive toxicity, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3

 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Repr. 2; H361d	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

DINITROL 6090

Revision: 04.12.2025

Product code: 5010

Page 14 of 14

H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)