

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

UFI: YGJP-T2YK-C00F-WT6N

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

Supplier

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229
 Eye Irrit. 2; H319
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 2 of 14

H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH208 Contains calcium sulfonate. May produce an allergic reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229-H412

Precautionary statements

P210-P211-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 3 of 14

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			25 - < 50 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304			
109-66-0	pentane			5 - < 10 %
	203-692-4	601-006-00-1	01-2119459286-30	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			5 - < 10 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
61789-86-4	calcium sulfonate			2,5 - < 5 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			
154518-38-4	Phosphorsäure, C11-14-Isoalkylester, C13-reich			< 2,5 %
	800-484-0		01-2119976356-25	
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411			
68526-86-3	Alcohols, C11-14-iso-, C13-rich			< 0,5 %
	271-235-6		01-2119454259-34	
	Aquatic Acute 1, Aquatic Chronic 2; H400 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	25 - < 50 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		
109-66-0	203-692-4	pentane	5 - < 10 %
	inhalation: LC50 = > 25,3 mg/l (vapours); oral: LD50 = >5000 mg/kg		
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	5 - < 10 %
	inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
61789-86-4	263-093-9	calcium sulfonate	2,5 - < 5 %
	dermal: LD50 = 4000 - 5000 mg/kg; oral: LD50 = 16000 mg/kg Skin Sens. 1B; H317: >= 10 - 100		
154518-38-4	800-484-0	Phosphorsäure, C11-14-Isoalkylester, C13-reich	< 2,5 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = > 2000 mg/kg		

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 4 of 14

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Provide fresh air.

After contact with skin

In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Extinguishing powder, Water spray jet, alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear personal protection equipment. Avoid contact with skin, eyes and clothes.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 5 of 14

6.4. Reference to other sections

Safe handling: see section 7
 Personal protection equipment: see section 8
 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.
 Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.
 Remove contaminated, saturated clothing immediately.
 Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
 Do not keep the container sealed. Keep container dry.
 Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
109-66-0	Pentane	600	1800		TWA (8 h)	WEL

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 6 of 14

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
109-66-0	pentane		
Worker DNEL, long-term	inhalation	systemic	3000 mg/m ³
Worker DNEL, long-term	dermal	systemic	432 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	643 mg/m ³
Consumer DNEL, long-term	dermal	systemic	214 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	214 mg/kg bw/day
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Worker DNEL, long-term	dermal	systemic	208 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	871 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	185 mg/m ³
Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	125 mg/kg bw/day
61789-86-4	calcium sulfonate		
Worker DNEL, long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term	dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term	dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	0,513 mg/cm ²
Consumer DNEL, long-term	oral	systemic	0,8333 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	11,75 mg/m ³

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 7 of 14

PNEC values

CAS No	Substance	Value
Environmental compartment		
109-66-0	pentane	
Freshwater		0,230 mg/l
Marine water		0,230 mg/l
Freshwater sediment		1,2 mg/kg
Marine sediment		1,2 mg/kg
Microorganisms in sewage treatment plants (STP)		3,600 mg/l
61789-86-4	calcium sulfonate	
Freshwater		1 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16667 mg/kg
Microorganisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment
Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

Thickness of the glove material : > 0,12 mm

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141),. Filter material/medium: A2/P3

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 8 of 14

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
 Colour: black
 Odour: characteristic
 Odour threshold: not determined

Test method

Melting point/freezing point: not determined
 Boiling point or initial boiling point and boiling range: not determined
 Flammability: not applicable
 Lower explosion limits: 0,6 vol. %
 Upper explosion limits: 10,9 vol. %
 Flash point: -97 °C
 Auto-ignition temperature: > 200 °C
 Decomposition temperature: not determined
 pH-Value: not determined
 Viscosity / kinematic: not determined
 Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents
 not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: 3500 hPa
 (at 20 °C)

Density (at 20 °C): 0,7 g/cm³ DIN 51757

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties
 not determined
 Sustained combustibility: No data available
 Self-ignition temperature
 Solid: not applicable
 Gas: not applicable
 Oxidizing properties
 not determined

Other safety characteristics

Evaporation rate: not determined
 Solvent content: 76,0 %
 Solid content: 21,9 %
 Viscosity / dynamic: not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 9 of 14

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
109-66-0	pentane				
	oral	LD50 >5000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 25,3 mg/l	Rat		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >5000 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 16000 mg/kg	Rat		
	dermal	LD50 4000 - 5000 mg/kg	Rabbit		
154518-38-4	Phosphorsäure, C11-14-Isoalkylester, C13-reich				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

Irritation and corrosivity

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 10 of 14

Serious eye damage/eye irritation: Causes serious eye irritation.
 Skin corrosion/irritation: Based on available data, the classification criteria are not met.
 Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.
 Contains calcium sulfonate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
 Carcinogenicity: Based on available data, the classification criteria are not met.
 Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
109-66-0	pentane					
	Acute fish toxicity	LC50 mg/l	4,26	96 h	fish	
	Acute crustacea toxicity	EC50	9,7 mg/l	48 h	Daphnia magna	IUCLID

12.2. Persistence and degradability

No further relevant information available.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	OECD 301F	> 60 %	28		
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.
 not applicable

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 11 of 14

12.7. Other adverse effects

No further relevant information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 12 of 14



Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

E0
 Passenger-LQ: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No
 Marine pollutant: no

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Stowage Code:
 SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:
 SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 29, Entry 40, Entry 75

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 13 of 14

Directive 2004/42/EC on VOC in paints and varnishes: 76,02 %
 552,7 g/l
 Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

Observe in addition any national regulations!
 Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Water hazard class (D): 2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,8,14.

Abbreviations and acronyms

- Aerosol 1: Aerosols, hazard category 1
- Flam. Liq. 2: Flammable liquids, hazard category 2
- Flam. Liq. 3: Flammable liquids, hazard category 3
- Asp. Tox. 1: Aspiration hazard, hazard category 1
- Skin Irrit. 2: Skin irritation, hazard category 2
- Eye Dam. 1: Serious eye damage, hazard category 1
- Eye Irrit. 2: Eye irritation, hazard category 2
- Skin Sens. 1B: Skin sensitisation, hazard category 1B
- STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
- Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
- Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
- Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

DINITROL HIGH PERFORMANCE WAX BLACK SPRAY

Revision: 09.03.2026

Product code: 30173

Page 14 of 14

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains calcium sulfonate. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)