

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

DINITROL Metallic Spray

UFI: 1T3D-JMUU-K007-HVX9

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Anti-corrosive coating

**Uses advised against**

No further relevant information available.

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

**Supplier**

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

**1.4. Emergency telephone number:** Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No 1272/2008**

Aerosol 1; H222-H229  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**Regulation (EC) No 1272/2008**

**Hazard components for labelling**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 2 of 13

H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Special labelling**

Restricted to professional users.

**Additional advice on labelling**

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

**Labelling of packages where the contents do not exceed 125 ml**
**Signal word:** Danger

**Pictograms:**

**Hazard statements**

H222-H229

**Precautionary statements**

P210-P251-P410+P412

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			40 - < 45 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Press. Gas (Comp.); H220 H280			
106-97-8	n-butane			10 - < 15 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Press. Gas (Comp.); H220 H280			
64-17-5	Ethanol			1 - < 5 %
	200-578-6		01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7429-90-5	aluminium powder (stabilised)			1 - < 5 %
	231-072-3	013-002-00-1	01-2119455851-35	
	Flam. Sol. 1, Water-react. 2; H228 H261			

Full text of H and EUH statements: see section 16.

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 3 of 13

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	40 - < 45 %
		inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64-17-5	200-578-6	Ethanol	1 - < 5 %
		inhalation: LC50 = > 50 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
7429-90-5	231-072-3	aluminium powder (stabilised)	1 - < 5 %
		inhalation: LC50 = >5 mg/l (dusts or mists)	

**Further Information**

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove contaminated, saturated clothing immediately.

**After inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. If unconscious but breathing normally, place in recovery position and seek medical advice.

**After contact with skin**

Wash with plenty of water/Soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Call a physician immediately. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Carbon dioxide (CO2), Foam, Extinguishing powder.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

No further relevant information available.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 4 of 13

surface water.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up**

**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).  
Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.  
Clear contaminated areas thoroughly.  
Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Not required.

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 5 of 13

**Further information on storage conditions**

Keep container tightly closed.

**7.3. Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
7429-90-5	Aluminium metal, respirable dust	-	4		TWA (8 h)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
1317-65-3	Calcium carbonate, respirable	-	4		TWA (8 h)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	Consumer DNEL, long-term	oral	systemic	125 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	208 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	871 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	systemic	185 mg/m <sup>3</sup>
64-17-5	Ethanol			
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	114 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	systemic	950 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	local	1900 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	local	950 mg/m <sup>3</sup>
7429-90-5	aluminium powder (stabilised)			
	Worker DNEL, long-term	inhalation	systemic	3,72 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	local	3,72 mg/m <sup>3</sup>
	Consumer DNEL, long-term	oral	systemic	3,95 mg/kg bw/day

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 6 of 13

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
64-17-5	Ethanol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
7429-90-5	aluminium powder (stabilised)	
Freshwater		0,0749 mg/l
Micro-organisms in sewage treatment plants (STP)		20 mg/l

**8.2. Exposure controls**



**Appropriate engineering controls**

Provide adequate ventilation.  
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.  
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Eye glasses with side protection (EN 166)

**Hand protection**

Recommended glove articles :  
 FKM (fluoro rubber), Breakthrough time:: 480 min.  
 NBR (Nitrile rubber), Breakthrough time:: 480 min.  
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
 Protective gloves have to be replaced at the first sign of deterioration.  
 Protect skin by using skin protective cream.

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.  
 gas filtering equipment (EN 141),. Filter material/medium: AX

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state: Aerosol  
 Colour: bronze  
 Odour: characteristic  
 Odour threshold: not determined

**Test method**

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 7 of 13

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-42 °C
Flammability:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	< - 20 °C DIN 53213
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	8300 hPa
(at 20 °C)	
Density (at 20 °C):	0,8 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not determined

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties	
not determined	
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

**Other safety characteristics**

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	68,9 %
Solid content:	30,1%
Viscosity / dynamic:	not determined

**Further Information**

No information available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No further relevant information available.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

No further relevant information available.

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 8 of 13

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Carbon monoxide

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 5000 mg/l	Rat		
64-17-5	Ethanol				
	oral	LD50 10470 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 50 mg/l	Rat		
7429-90-5	aluminium powder (stabilised)				
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 9 of 13

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information**
**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	Ethanol					
	Acute algae toxicity	ErC50 275 mg/l	72 h	Chlorella vulgaris		
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)		

**12.2. Persistence and degradability**

No further relevant information available.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
		80%			
	Readily biodegradable (according to OECD criteria).				

**12.3. Bioaccumulative potential**

No further relevant information available.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36

**12.4. Mobility in soil**

No further relevant information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No further relevant information available.

**Further information**

No further relevant information available.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 10 of 13

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Remove according to the regulations.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

**Other applicable information (land transport)**

E0

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Limited quantity: 1 L  
 Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: yes  
 Special Provisions: 63, 190, 277, 327, 344, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 11 of 13

EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, FLAMMABLE  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg

**Other applicable information (air transport)**

E0  
 Passenger-LQ: Y203

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, aliphatic

**14.6. Special precautions for user**

Warning gas

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**Other applicable information**

SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1litre: Category A.  
 For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS:  
 Category C, Clear of living quarters.  
 SG69 For AEROSOLS with a maximum capacity of 1 litre:  
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
 For AEROSOLS with a capacity above 1 litre:  
 Segregation as for the appropriate subdivision of class 2.  
 For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 29, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 68,67 %  
 516,4 g/l  
 Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

**Additional information**

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 12 of 13

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

**Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

86164

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics

**SECTION 16: Other information**
**Changes**

This data sheet contains changes from the previous version in section(s): 9.

**Abbreviations and acronyms**

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases, hazard category 2

Flam. Gas 1A: Flammable gases, hazard category 1A

Aerosol 1: Aerosols, hazard category 1

Press. Gas (Comp.): Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, hazard category 2

Flam. Liq. 3: Flammable liquids, hazard category 3

Flam. Sol. 1: Flammable solids, hazard category 1

Asp. Tox. 1: Aspiration hazard, hazard category 1

Eye Irrit. 2: Eye irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
STOT SE 3; H336	Bridging principle "Aerosols"

**Relevant H and EUH statements (number and full text)**

H220 Extremely flammable gas.  
 H222 Extremely flammable aerosol.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.

**DINITROL Metallic Spray**

Revision: 26.02.2026

Product code: 21705

Page 13 of 13

H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H261	In contact with water releases flammable gases.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*