

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 1 of 11

**1. Identification**
**Product identifier**

DINITROL 4010 Spray

**Recommended use of the chemical and restrictions on use**
**Use of the substance/mixture**

Anti-corrosive coating

**Uses advised against**

No further relevant information available.

**Details of the supplier of the safety data sheet**
**Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

**Supplier**


Company name:	DINOL U.S. Inc.	
Street:	8500 Cotter Street, Lewis Center	
Place:	USA-43035 Ohio	
Telephone:	740-548-1656	Telefax: 740-548-1657
E-mail:	info@dinolus.com	
Internet:	www.dinol.com	

**Emergency phone number:** 3E Company Emergency +1-866-404-4230

**2. Hazard(s) identification**
**Classification of the chemical**
**29 CFR Part 1910.1200**

Flammable aerosols: Category 1  
 Gases under pressure: Compressed gas  
 Respiratory or skin sensitization: Skin sensitization, category 1  
 Specific target organ toxicity single exposure: Category 3 (narcotic effects)  
 Specific target organ toxicity repeated or prolonged exposure: Category 1  
 Aspiration hazard: Category 1

**Label elements**
**29 CFR Part 1910.1200**
**Signal word:** Danger

**Pictograms:**

**Hazard statements**

Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated  
 May be fatal if swallowed and enters airways

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 4010 Spray

Revision date: 06/09/2026

Product code: 21703

Page 2 of 11

May cause an allergic skin reaction  
 May cause drowsiness or dizziness  
 Causes damage to organs through prolonged or repeated exposure

#### Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Do not eat, drink or smoke when using this product.  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If swallowed: Immediately call a poison center/doctor.  
 Do NOT induce vomiting.  
 If on skin: Wash with plenty of Water and soap.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 Call a poison center/doctor if you feel unwell.  
 Get medical advice/attention if you feel unwell.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

#### Hazards not otherwise classified

No information available.

### 3. Composition/information on ingredients

#### Mixtures

##### Relevant ingredients

CAS No	Components	Quantity
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	19.9 %
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	19.9 %
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	9.9 %
61789-86-4	calcium sulfonate	5 %
	calcium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	2.4 %

#### Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).  
 According to the current Annex II of the REACH Regulation, the concentration of the substances contained in the mixture is indicated. When classifying aerosols, the values used for calculation may differ.

### 4. First-aid measures

#### Description of first aid measures

##### General information

Remove contaminated, saturated clothing immediately.

##### After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 4010 Spray

Revision date: 06/09/2026

Product code: 21703

Page 3 of 11

necessary. If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After contact with skin

Wash with plenty of water/Soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

#### Most important symptoms and effects, both acute and delayed

Disorientation Nausea, Dizziness, Headache.

#### Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5. Fire-fighting measures

### Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

#### Unsuitable extinguishing media

High power water jet.

### Specific hazards arising from the chemical

Flammable. Vapors may form explosive mixtures with air.

In case of fire may be liberated: Gases/vapors, toxic

### Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

### Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapors/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition.

Do not breathe gas/fume/vapor/spray.

Avoid contact with skin, eyes and clothes.

Use personal protection equipment.

#### For emergency responders

For further specification, refer to section 8 of the SDS.

### Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 4 of 11

**For cleaning up**

Provide adequate ventilation.  
Clear contaminated areas thoroughly.  
Do not rinse down with water.

**Other information**

No information available.

**Reference to other sections**

Safe handling: see section 7  
Personal protection equipment (PPE): see section 8  
Disposal: see section 13

**7. Handling and storage**
**Precautions for safe handling**
**Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fume/vapor/spray.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.  
Take precautionary measures against static discharges.  
Vapors may form explosive mixtures with air.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Conditions for safe storage, including any incompatibilities**
**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Not required.

**Further information on storage conditions**

Keep container tightly closed.

**8. Exposure controls/personal protection**
**Control parameters**
**Exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	Category	Origin
75-28-5	Butane: isobutane	1000	2370	STEL (15 min)	ACGIH-2025
106-97-8	Butane: n-butane	1000	2370	STEL (15 min)	ACGIH-2025
75-28-5	Isobutane	800	1900	TWA (8 h)	REL
106-97-8	n-Butane	800	1900	TWA (8 h)	REL
74-98-6	Propane	1000	1800	TWA (8 h)	PEL
		1000	1800	TWA (8 h)	REL
		-	-	Asphyxiant	ACGIH-2025

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 5 of 11

**Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Eye glasses with side protection (EN 166)

**Hand protection**

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

Thickness of the glove material : &gt; 0,12 mm

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141),. Filter material/medium: AX (short-term)

**9. Physical and chemical properties**
**Information on basic physical and chemical properties**

Physical state:	Aerosol
Color:	transparent beige
Odor:	characteristic
Odour threshold:	not determined
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	Not applicable, as it is an aerosol.
Flammability:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	Not applicable, as it is an aerosol.
Auto-ignition temperature:	240 °C
Decomposition temperature:	not determined
pH-Value:	The study does not need to be conducted because the substance is known to be insoluble in water.
Viscosity / kinematic:	not determined
Water solubility:	not applicable
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 6 of 11

Vapor pressure: (at 20 °C)	3500 hPa
Density (at 20 °C):	0,7 g/cm <sup>3</sup>
Relative vapour density:	not determined
Particle characteristics:	not applicable

**Other information**
**Information with regard to physical hazard classes**

Explosive properties	not determined
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

**Other safety characteristics**

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	66,3 %
Solid content:	31,7 %
Viscosity / dynamic:	not determined

**Further Information**

No information available.

**10. Stability and reactivity**
**Reactivity**

No further relevant information available.

**Chemical stability**

Stability: Stable

The product is stable under storage at normal ambient temperatures.

**Possibility of hazardous reactions**

Hazardous reactions: Will not occur

No known hazardous reactions.

**Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapors may form explosive mixtures with air.

**Incompatible materials**

Oxidizing agent, strong

**Hazardous decomposition products**

Carbon monoxide

**11. Toxicological information**
**Information on toxicological effects**
**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation gas) &gt; 20000 ppm

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 7 of 11

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50 >15000 mg/kg	Rat		
	dermal	LD50 >3400 mg/kg	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation vapour	LC50 >5000 mg/l	Rat		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 5000 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 16000 mg/kg	Rat		
	dermal	LD50 4000 - 5000 mg/kg	Rabbit		
	calcium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 > 20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 18 mg/l	Rat		

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitizing effects**

May cause an allergic skin reaction (calcium sulfonate)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure**

May cause drowsiness or dizziness (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%);

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics)

**Specific target organ toxicity (STOT) - repeated exposure**

Causes damage to organs through prolonged or repeated exposure (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

**Aspiration hazard**

May be fatal if swallowed and enters airways

**Information on other hazards**

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 8 of 11

**Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**Further information**

There are no data available on the preparation/mixture itself.

**12. Ecological information**
**Persistence and degradability**

The product has not been tested.

**Bioaccumulative potential**

The product has not been tested.

**Mobility in soil**

There are no data available on the mixture itself.

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other adverse effects**

No further relevant information available.

**Further information**

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**13. Disposal considerations**
**Waste treatment methods**
**Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes. Do not allow to enter into surface water or drains.

List of proposed waste codes/waste designations in accordance with EWC:

**Contaminated packaging**

Remove according to the regulations.

**14. Transport information**
**U.S. DOT 49 CFR 172.101**
**UN number or ID number:**

UN 1950

**Proper shipping name:**

Coating solution

**Transport hazard class(es):**

2

Hazard label:

2.1


**Marine transport (IMDG)**
**UN number or ID number:**

UN 1950

**UN proper shipping name:**

AEROSOLS

**Transport hazard class(es):**

2.1

**Packing group:**

-

Hazard label:

2.1



**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 9 of 11

Marine pollutant:	no
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

<b>UN number or ID number:</b>	UN 1950
<b>UN proper shipping name:</b>	AEROSOLS, FLAMMABLE
<b>Transport hazard class(es):</b>	2.1
<b>Packing group:</b>	-
Hazard label:	2.1



Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**Other applicable information (air transport)**

E0  
Passenger-LQ: Y203

**Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**Special precautions for user**

Warning : gas

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Other applicable information**

SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
SG69 For AEROSOLS with a maximum capacity of 1litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

**15. Regulatory information**
**U.S. Regulations**
**National Inventory TSCA**

Substance/product listed in the following inventories: TSCA

**National regulatory information**

SARA Section 311/312 Hazards:

Propane (74-98-6): Fire hazard, Sudden release of pressure  
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (-): Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard  
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics (-): Fire hazard, Immediate (acute) health hazard

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 10 of 11

Butane (106-97-8): Fire hazard, Sudden release of pressure  
 Isobutane (75-28-5): Fire hazard, Sudden release of pressure  
 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (-): Fire hazard, Immediate (acute) health hazard  
 calcium sulfonate (61789-86-4): Immediate (acute) health hazard  
 calcium bis (di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate) (-): Immediate (acute) health hazard  
 Clean Air Act Section 112(r):  
 Propane (74-98-6): Threshold quantities = 10,000 lbs.  
 Butane (106-97-8): Threshold quantities = 10,000 lbs.  
 Isobutane (75-28-5): Threshold quantities = 10,000 lbs.

**State Regulations**
**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Directive 2004/42/EC on VOC in paints and varnishes: 66,33 %  
 490,2 g/l

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

55214

**16. Other information**
**Hazardous Materials Identification System (HMIS)**

Health: 0  
 Flammability: 4  
 Physical Hazard: 3

**NFPA Hazard Ratings**

Health: 0  
 Flammability: 4  
 Reactivity: 3  
 Unique Hazard: none


**Changes**

Revision date: 06/09/2026  
 Revision No: 2,0

This data sheet contains changes from the previous version in section(s): 2,3,9,16.

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

**Other data**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 4010 Spray**

Revision date: 06/09/2026

Product code: 21703

Page 11 of 11

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*