

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 1 of 15

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

DINITROL SOM 1

UFI: HYEP-D5DE-G10U-1GT5

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Anti-corrosive coating

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Internet:	www.dinol.com	
Responsible Department:	msds@dinol.com	

**Supplier**

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

**1.4. Emergency telephone number:**

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226  
 STOT SE 3; H336  
 STOT RE 1; H372  
 Asp. Tox. 1; H304  
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**Regulation (EC) No 1272/2008**

**Hazard components for labelling**

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  
 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  
 Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

**Pictograms:**



**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 2 of 15

**Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains calcium sulfonate, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Special labelling**

Restricted to professional users.

**Labelling of packages where the contents do not exceed 125 ml**
**Signal word:** Danger

**Pictograms:**

**Hazard statements**

H304-H372-H412

**Precautionary statements**

P260-P405

**2.3. Other hazards**

Hydrocarbons meet the requirements for not being classified as carcinogenic (&lt;0,1% benzene alt&lt;3% (w/w) DMSO extract (IP 346)).

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 3 of 15

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			20 - < 25 %
	919-446-0		01-2119458049-33	
	Flam. Liq. 3, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H372 H304 H411 EUH066			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			20 - < 25 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			20 - < 25 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
61789-86-4	calcium sulfonate			5 - < 10 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			
1474044-79-5	Naphthalenesulfonic acid, di-C9-rich C8-10-branched alkyl derivs., calcium salts			1 - < 5 %
	939-717-7		01-2119980985-16	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
136-52-7	cobalt bis(2-ethylhexanoate)			< 0.1 %
	205-250-6		01-2119524678-29	
	Repr. 1A, Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 3; H360Fd H312 H302 H319 H317 H400 H412			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-446-0	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	20 - < 25 %
	dermal: LD50 = >3400 mg/kg; oral: LD50 = >15000 mg/kg		
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	20 - < 25 %
	inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	20 - < 25 %
	inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
61789-86-4	263-093-9	calcium sulfonate	5 - < 10 %
	dermal: LD50 = 4000 - 5000 mg/kg; oral: LD50 = 16000 mg/kg Skin Sens. 1B; H317: >= 10 - 100		
136-52-7	205-250-6	cobalt bis(2-ethylhexanoate)	< 0.1 %
	dermal: LD50 = 1244 mg/kg; oral: LD50 = 2000 mg/kg Aquatic Acute 1; H400: M=10		

**Further Information**

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 4 of 15

**General information**

Remove contaminated, saturated clothing immediately.

**After inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. If unconscious but breathing normally, place in recovery position and seek medical advice.

**After contact with skin**

Wash with plenty of water/Soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Nausea, Dizziness, Headache.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures**
**5.1. Extinguishing media**
**Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**
**6.1. Personal precautions, protective equipment and emergency procedures**
**General advice**

Remove all sources of ignition.  
Do not breathe gas/fumes/vapour/spray.  
Avoid contact with skin, eyes and clothes.  
Use personal protection equipment.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**
**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 5 of 15

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

- Provide adequate ventilation.
- Clear contaminated areas thoroughly.
- Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

- Keep away from sources of ignition - No smoking.
- Take precautionary measures against static discharges.
- Vapours can form explosive mixtures with air.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Not required.

**Further information on storage conditions**

No information available.

**7.3. Specific end use(s)**

Anti-corrosive coating

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 6 of 15

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
Worker DNEL, long-term	inhalation	systemic	330 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	44 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	71 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	26 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Consumer DNEL, long-term	oral	systemic	125 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	871 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	systemic	185 mg/m <sup>3</sup>
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Worker DNEL, long-term	inhalation	systemic	871 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	185 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	46 mg/kg bw/day
61789-86-4	calcium sulfonate		
Worker DNEL, long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term	dermal	local	1,03 mg/cm <sup>2</sup>
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	0,513 mg/cm <sup>2</sup>
Consumer DNEL, long-term	oral	systemic	0,8333 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	11,75 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	
Environmental compartment	Value	
61789-86-4	calcium sulfonate	
Freshwater	1 mg/l	
Marine water	1 mg/l	
Freshwater sediment	226000000 mg/kg	
Marine sediment	226000000 mg/kg	
Secondary poisoning	16667 mg/kg	
Microorganisms in sewage treatment plants (STP)	1000 mg/l	
Soil	271000000 mg/kg	

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 7 of 15

**8.2. Exposure controls**



**Appropriate engineering controls**

Provide adequate ventilation.  
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.  
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Eye glasses with side protection (DIN EN 166)

**Hand protection**

Tested protective gloves must be worn (EN ISO 374):  
 FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.  
 NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.  
 Thickness of the glove material : > 0,12 mm  
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
 Protective gloves have to be replaced at the first sign of deterioration.  
 Protect skin by using skin protective cream.

**Skin protection**

Wear anti-static footwear and clothing

**Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection.  
 gas filtering equipment (EN 141),. Filter material/medium: A

**Thermal hazards**

No information available.

**Environmental exposure controls**

No information available.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light brown
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	136 - 164 °C
Flammability:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	7,0 vol. %
Flash point:	36 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined

**Test method**

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 8 of 15

Viscosity / kinematic: (at 40 °C)	< 20,5 mm <sup>2</sup> /s
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	5 hPa
Vapour pressure: (at 50 °C)	30 hPa
Density (at 20 °C):	0,87 - 0,91 g/cm <sup>3</sup>
Relative vapour density:	not determined
Particle characteristics:	not applicable

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties not determined	
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties not determined	

**Other safety characteristics**

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	51,9 %
Solid content:	47 - 51 %
Softening point:	not determined
Viscosity / dynamic:	not determined
Flow time: (at 20 °C)	18 - 26 4 DIN EN ISO 2431

**Further Information**

No information available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No further relevant information available.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

No further relevant information available.

**10.5. Incompatible materials**

No further relevant information available.

**10.6. Hazardous decomposition products**

Carbon monoxide

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 9 of 15

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes**
**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50 >15000 mg/kg	Rat		
	dermal	LD50 >3400 mg/kg	Rat		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 5000 mg/l	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation vapour	LC50 >5000 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 16000 mg/kg	Rat		
	dermal	LD50 4000 - 5000 mg/kg	Rabbit		
136-52-7	cobalt bis(2-ethylhexanoate)				
	oral	LD50 2000 mg/kg	Rat		
	dermal	LD50 1244 mg/kg	Rabbit		

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

Based on available data, the classification criteria are not met.

Contains calcium sulfonate, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 10 of 15

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

**STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

No information available.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)					
	Acute fish toxicity	LL50 mg/l	10-30	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	4,6 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EL50 mg/l	10-22	48 h	Daphnia magna (Big water flea)	

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 11 of 15

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
		74,7 %	28	
	Leicht biologisch abbaubar			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
		80%		
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	OECD 301F	> 60 %	28	
	Leicht biologisch abbaubar (nach OECD-Kriterien).			

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**Contaminated packaging**

Remove according to the regulations.

**SECTION 14: Transport information**
**Land transport (ADR/RID)**
**14.1. UN number or ID number:**

UN 1139

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 12 of 15

**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L  
Excepted quantity: E1  
Transport category: 3  
Hazard No: 30  
Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** Coating solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L  
Excepted quantity: E1

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: 955  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 13 of 15

IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	No
Marine pollutant:	no

**14.6. Special precautions for user**

Warning : Flammable liquids

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes:	51,88 % 461,7 g/l
Subcategory according to Directive 2004/42/EC:	Special finishes - All types, VOC limit value: 840 g/l

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

**National regulatory information**

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	3 - highly hazardous to water

**Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

667136

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

- Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
- Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
- Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

**SECTION 16: Other information**
**Changes**

This data sheet contains changes from the previous version in section(s): 2,11.

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 14 of 15

**Abbreviations and acronyms**

Flam. Liq. 3: Flammable liquids, hazard category 3  
 Acute Tox. 4: Acute toxicity, hazard category 4  
 Asp. Tox. 1: Aspiration hazard, hazard category 1  
 Skin Irrit. 2: Skin irritation, hazard category 2  
 Eye Irrit. 2: Eye irritation, hazard category 2  
 Skin Sens. 1A: Skin sensitisation, hazard category 1A  
 Skin Sens. 1B: Skin sensitisation, hazard category 1B  
 Repr. 1A: Reproductive toxicity, hazard category 1A  
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3  
 STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method
STOT RE 1; H372	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains calcium sulfonate, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of

**DINITROL SOM 1**

Revision: 09.06.2026

Product code: 21614

Page 15 of 15

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet contains only safety-related information and does not replace product information or product specifications.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*