PROTECTING

DINITROL SIM CLEANER

Crack Indication



DINITROL SIM CLEANER is a solvent borne cleaner used as the first step in the SIM crack indication system used for all types of metal, glass, ceramics and most types of plastic. Use the three components in combination to locate cracks or pores.

- » Transparent
- » Part of the crack indication SIM System
- » Cleans all residues
- » Clear liquid
- » Remains in cracks

DINITROL SIM CLEANER

Art. No.	Size	Package	Color
11211	400 ml	Spray can	Transparent

a brand of DINOL

DINOL GmbH Pyrmonter Straße 76, D-32676 Lügde, Germany
Tel. +49 (0) 5281-98 2 98-0, Fax +49 (0) 5281-98 2 98-60, www.dinol.com

11.2026

All data and recommendations are the result of careful tests by our laboratory. They only can be considered as recommendation which corresponds to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the misuse of our products. Therefore, a contractual legal relationship is not justified, and there are no secondary obligations arising from any purchase contracts.

PROTECTING

DINITROL SIM CLEANER

Technical Details

Product description
DINITROL SIM CLEANER is a solvent borne cleaner used as the first step in the SIM crack indication system used for all types of metal, glass, ceramics and most types of plastic. Use the three components in combination to locate cracks or pores.

Applications
DINITROL SIM CLEANER is used for cleaning surfaces to be checked for cracks.

Method of Use
DINITROL SIM CLEANER is applied by spraying from the spray can.

Pre-treatment substrates
DINITROL SIM CLEANER is applied directly to metal surfaces. For additional information, please consult DINOL GmbH.

Storage
The product should be stored at temperatures between +10°C and +30°C. Stored in a cool and dry place, the product has a shelf life of at least 2 years in the unopened original packaging.

Safety precautions
Additional information can be found in the safety data sheet.

Transportation
Additional information can be found in the safety data sheet.

Technical Data

Colour	transparent
Apppearance	fluid
Density at 23°C	880 kg/m^3
Recommended film thickness wet	100 µm (liter) / 200 µm (spray)
Flash point of active content	> 50°C
Flash point of spray content	> 0°C
Available in	400 ml Spray can

Hazards identification
2.1. Classification of the substance or mixture
GB CLP Regulation
Aerosol 1; H222-H229; Eye Irrit. 2; H319,
STOT SE 3; H336; Aquatic Chronic 2; H411

For all relevant safety advices please read the material safety data sheet or the packaging label.

All data and recommendations are the result of careful tests by our laboratory. They only can be considered as recommendation which corresponds to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the misuse of our products. Therefore, a contractual legal relationship is not justified, and there are no secondary obligations arising from any purchase contracts.