PROTECTING

# DINITROL SIM INDICATOR

## Crack Indicator




DINITROL SIM INDICATOR is a colour intensive solution used as the second step in the SIM crack indication system used for all types of metal, glass, ceramics and most types of plastic. Use the three components in combination to locate cracks or pores.

- » Red
- » Part of the crack indication SIM System
- » Stays in cracks

### DINITROL SIM INDICATOR

| Art. No. | Size | Package | Color |
|---|---|---|---|
| 11213 | 400 ml | Spray can | Red |

a brand of DINOL

**DINOL GmbH** Pyrmonter Straße 76, D-32676 Lügde, Germany
Tel. +49 (0) 5281-98 2 98-0, Fax +49 (0) 5281-98 2 98-60, www.dinol.com

11.2026

All data and recommendations are the result of careful tests by our laboratory. They only can be considered as recommendation which corresponds to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the misuse of our products. Therefore, a contractual legal relationship is not justified, and there are no secondary obligations arising from any purchase contracts.

PROTECTING

# DINITROL SIM INDICATOR

## Technical Details

**Product description**
DINITROL SIM INDICATOR is a colour intensive solution used as the second step in the SIM crack indication system used for all types of metal, glass, ceramics and most types of plastic. Use the three components in combination to locate cracks or pores.

**Applications**
DINITROL SIM INDICATOR is used as the second step in the crack indication system.

**Method of Use**
DINITROL SIM INDICATOR is applied by spraying.

**Pre-treatment substrates**
DINITROL SIM INDICATOR is applied on surfaces cleaned with DINITROL SIM Cleaner. For additional information, please consult DINOL GmbH.

**Storage**
The product should be stored at temperatures between +10°C and +30°C. Stored in a cool and dry place, the product has a shelf life of at least 2 years in the unopened original packaging.

**Safety precautions**
Additional information can be found in the safety data sheet.

**Transportation**
Additional information can be found in the safety data sheet.

## Technical Data

| | |
|---|---|
| Colour | intensive red |
| Apppearance | fluid |
| Density at 23°C | 880 kg/m$^3$ |
| Recommended film thickness wet | 100 µm (Liter) / 200 µm (Spray) |
| Flash point of active content | > 50°C |
| Flash point of spray content | > 0°C |
| Available in | 400 ml Spray can / 208 L Drum |

**Hazards identification**
**2.1. Classification of the substance or mixture**
GB CLP Regulation
Aerosol 1; H222-H229; Acute Tox. 4; H332;
Skin Irrit. 2; H315; Eye Irrit. 2; H319; STOT SE 3; H336

**For all relevant safety advices please read the material safety data sheet or the packaging label.**

All data and recommendations are the result of careful tests by our laboratory. They only can be considered as recommendation which corresponds to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the misuse of our products. Therefore, a contractual legal relationship is not justified, and there are no secondary obligations arising from any purchase contracts.